Firma: PC COOL DOO
Adresa: Višegradska 26A
Telefon: 0653526116
Fax:
PIB: 104045201
E-mail: info@pccool.rs

SSD M.2 NVMe Intenso PCIe 3x4 1TB read 2100write 1700

Šifra: 100538
Kategorija prozivoda: Hard disk HDD - SSD
Proizvođač: INTENSO

Cena: 17.780,00



Form factor: m.2 2280
Protocol: PCI Express (PCIe) Gen.3x4 NVME 1.3
Sequential writing: Up to 1700 MB/s

TBW: 600 TB
Features: SMART & TRIM Command Support

Interface: m.2
Sequential reading: Up to 2100 MB/s
MTBF: 1.500.000 hours
Properties: Advanced 3D-Nand technology with SLC data boost-cache

Specs

Features
NVMe version
1.3
SSD capacity
The Solid State Drive's data storage capacity.
2 TB
SSD form factor
The size of the solid-state drive, given in inches
M.2
Interface
Interface ports to connect pieces of equipment. USB (Universal Serial Bus) has become the most popular wired interface to connect peripherals. USB 2.0 supports speeds up to 480 Mbit/s (USB 1: 12 Mbit/s). The interface FireWire is also known as the IEEE 1394 standard. Enhanced IDE (EIDE)is sometimes referred to as Fast ATA, Fast IDE or ATA-2.
PCI Express 3.0
NVMe
NVM Express (NVMe) or Non-Volatile Memory Host Controller Interface Specification (NVMHCIS) is an open logical device interface specification for accessing non-volatile storage media attached via a PCI Express (PCIe) bus. NVM Express, as a logical device interface, has been designed to capitalize on the low latency and internal parallelism of solid-state storage devices.

Memory type
Type of memory in the device e.g. DDR3, SRAM (Static RAM).
3D NAND
Component for
What this product is used as a part of (component for).
PC
M.2 SSD size
2280 (22 x 80 mm)
Read speed
The speed at which a device can read data.
2100 MB/s
Write speed
The speed at which a device can write data.
1700 MB/s
PCI Express interface data lanes
x4
S.M.A.R.T. support

TRIM support

Mean time between failures (MTBF)
Statistical model used to indicate product/mechanism reliability; expressed in hours and percentage of duty cycle. This number (in hours) does not indicate the mean time before failure for a single unit/mechanism.
1500000 h
Protection features
Physical effects from which the product is protected e.g. water resistant, crash proof.
Shock resistant

Features
TBW rating
1200
Brand-specific features
Brand specific technologies
SLC Caching
Weight & dimensions
Width
The measurement or extent of something from side to side.
22 mm
Depth
The distance from the front to the back of something.
4 mm
Height
The measurement of the product from head to foot or from base to top.
80 mm
Weight
Weight of the product without packaging (net weight). If possible, the net weight is given including standard accessories and supplies. Please note that sometimes the manufacturer leaves out the weight of accessories and/or supplies.
6 g
Packaging data
Package width
The distance from one side of the packaging to the other.
171 mm
Package depth
The distance from the front to the back of the packaging.
117 mm
Package height
The distance from the top to the bottom of the packaging.
25 mm
Package weight
Weight of the packaged product.

Cene su informativnog karaktera. Prodavac ne odgovara za tačnost cena iskazanih na sajtu, zadržava pravo izmena cena. Ponudu za ostale artikle, informacije o stanju lagera i aktuelnim cenama možete dobiti na upit. Plaćanje se isključivo vrši virmanski - bezgotovinski.