
Firma: PC COOL DOO
Adresa: Višegradska 26A
Telefon: 0653526116
Fax:
PIB: 104045201
E-mail: info@pccool.rs

Matična ploca Gigabyte AM5 X870 A TACHYON ICE

Šifra: 102862
Kategorija prozivoda: Matične ploče
Proizvođač: GIGABYTE

Cena: 64.860,00



Procesorsko podnožje (Socket)	AMD Socket AM5
Skup čipova (Chipset)	AMD X870
Podrška za procesore	AMD Ryzen 9000 Series Processors AMD Ryzen 8000 Series Processors AMD Ryzen 7000 Series Processors
Tip memorije (RAM)	DDR5
Broj memorijskih slotova	2x 288-Pin DDR5
Podrška za memorije	Support for DDR5 9600(OC)/ 9200(OC)/ 8800(OC)/ 8600(OC)/ 8400(OC)/ 8200(OC)/ 8000(OC)/ 7800(OC)/ 7600(OC)/ 7200(OC)/ 7000(OC)/ 6800(OC)/ 6666(OC)/ 6600(OC)/ 6400(OC)/ 6200(OC)/ 6000(OC)/ 5600(OC)/ 5200/ 4800/ 4400 MT/s memory modules 2 x DDR5 DIMM sockets supporting up to 128 GB (64 GB single DIMM capacity)of system memory Dual channel memory architecture Support for ECC and non-ECC Un-buffered DIMM memory modules Support for AMD EXtended Profiles for Overclocking (AMD EXPO) and ExtremeMemory Profile (XMP) memory modules
Podrška za grafiku - portovi	Integrated Graphics Processor with AMD Radeon Graphics support+ASMedia USB4 Controller: - 1 x USB4 USB Type-C port, supporting USB4 and DisplayPort video outputs and a maximum resolution of 3840x2160 240Hz Support for DisplayPort 1.4 version and HDR. Integrated Graphics Processor with AMD Radeon Graphics support: - 1 x HDMI port, supporting a maximum resolution of 4096x2160 60Hz Support for HDMI 2.1 version, HDCP 2.3, and HDR. Support for native HDMI 2.1 TMDS compatible ports. - 1 x front HDMI port, supporting a maximum resolution of 1920x1080 30Hz Support for HDMI 1.4 version.
Slotovi za proširenja	1 x PCI Express x16 slot (PCIEX16), integrated in the CPU: - AMD Ryzen 9000/7000 Series Processors support PCIe 5.0 x16 mode - AMD Ryzen 8000 Series-Phoenix 1 Processors support PCIe 4.0 x8 mode - AMD Ryzen 8000 Series-Phoenix 2 Processors support PCIe 4.0 x4

	mode 1 x PCI Express x16 slot (PCIEX8), integrated in the CPU: - AMD Ryzen 9000/7000 Series Processors support PCIe 5.0 x8 mode
M.2 portovi	3x M.2 Socket 3
Čuvanje podataka - portovi	1 x M.2 connector (M2A_CPU), integrated in the CPU, supporting Socket 3, M key, type 25110/22110/2580/2280 SSDs: - AMD Ryzen 9000/7000 Series Processors support PCIe 5.0 x4/x2 SSDs - AMD Ryzen 8000 Series-Phoenix 1 Processors support PCIe 4.0 x4/x2 SSDs - AMD Ryzen 8000 Series-Phoenix 2 Processors support PCIe 4.0 x4/x2 SSDs 1 x M.2 connector (M2D_SB), integrated in the Chipset, supporting Socket 3, M key, type 22110/2280 PCIe 4.0 x2 SSDs 1 x M.2 connector (M2B_SB), integrated in the Chipset, supporting Socket 3, M key, type 22110/2280 PCIe 4.0 x4/x2 SSDs 4 x SATA 6Gb/s connectors RAID 0, RAID 1, RAID 5, and RAID 10 support for NVMe SSD storage devices RAID 5 is only available on AMD Ryzen 9000 Series Processors. RAID 0, RAID 1, and RAID 10 support for SATA storage devices
SATA portovi	4x SATA 6Gb/s
LAN	Realtek 5GbE LAN chip (5 Gbps/2.5 Gbps/1 Gbps/100 Mbps)
Bežična mreža	Realtek Wi-Fi 7 RTL8922AE - 802.11a, b, g, n, ac, ax, be, supporting 2.4/5/6 GHz carrier frequency bands - Support for 11be 160MHz wireless standard (Actual data rate may vary depending on environment and equipment.)
Bluetooth	BLUETOOTH 5.4
Zvuk (Audio)	Realtek ALC1220 CODEC The back panel line out jack supports DSD audio. High Definition Audio 2/4/5.1/7.1-channel You can change the functionality of an audio jack using the audio software. To configure 7.1-channel audio, access the audio software for audio settings. Support for S/PDIF Out
USB portovi	**CPU+ASMedia USB4 controller: **- 1 x USB4 USB Type-C port on the back panel **CPU: **- 2 x USB 3.2 Gen 2 Type-A ports (red) on the back panel **Chipset+USB 3.2 Gen 1 Hub: **- 4 x USB 3.2 Gen 1 ports on the back panel **Chipset: **- 1 x USB Type-C port with USB 3.2 Gen 2x2 support, available through the internal USB header - 1 x USB 3.2 Gen 2 Type-A port (red) on the back panel - 2 x USB 3.2 Gen 1 ports available through the internal USB header - 4 x USB 2.0/1.1 ports available through the internal USB headers
Konektori na zadnjoj strani	1 x Q-Flash Plus button 1 x OC Ignition button 1 x PS/2 keyboard port 1 x PS/2 mouse port 1 x HDMI port (Note) 4 x USB 3.2 Gen 1 ports 3 x USB 3.2 Gen 2 Type-A ports (red) 1 x USB4 USB Type-C port (DisplayPort (Note)) 1 x RJ-45 port 2 x antenna connectors (2T2R) 2 x audio jacks 1 x optical S/PDIF Out connector

Unutrašnji konektori	1 x 24-pin ATX main power connector 2 x 8-pin ATX 12V power connectors 1 x CPU fan header 1 x CPU fan/water cooling pump header 4 x system fan headers 2 x system fan/water cooling pump headers 3 x addressable RGB Gen2 LED strip headers 1 x RGB LED strip header 3 x M.2 Socket 3 connectors 4 x SATA 6Gb/s connectors 1 x front panel header 1 x front panel audio header 1 x USB Type-C header, with USB 3.2 Gen 2x2 support 1 x USB 3.2 Gen 1 header 2 x USB 2.0/1.1 headers 1 x noise detection header 1 x Trusted Platform Module header (For the GC-TPM2.0 SPI V2 module only) 1 x HDMI port (Note) 1 x reset jumper 1 x Clear CMOS jumper 2 x temperature sensor headers 1 x power button (PWR) 1 x reset button(RESET) 1 x Clear CMOS button (CMOS) 1 x Cold Reset button (RTY) 1 x CPU Clock up button (ECLK+) 1 x CPU Clock down button (ECLK-) 1 x BIOS switch (BIOS_SW) 1 x OC Trigger switch (TGR_SW) Voltage Measurement Points
Posebne mogućnosti	Support for GIGABYTE Control Center (GCC) Support for Q-Flash Support for Q-Flash Plus Support for Smart Backup
Operativni sistem	Windows 11
BIOS	2 x 256 Mbit flash Use of licensed AMI UEFI BIOS Support for DualBIOS PnP 1.0a, DMI 2.7, WfM 2.0, SM BIOS 2.7, ACPI 5.0

Cene su informativnog karaktera. Prodavac ne odgovara za tačnost cena iskazanih na sajtu, zadržava pravo izmena cena. Ponudu za ostale artikle, informacije o stanju lagera i aktuelnim cenama možete dobiti na upit. Plaćanje se isključivo vrši virmanski - bezgotovinski.