Firma: PC COOL DOO
Adresa: Višegradska 26A
Telefon: 0653526116
Fax:
PIB: 104045201
E-mail: info@pccool.rs

Matična ploča AM4 Gigabyte A520M H RGB DVIHDMIM.2

Šifra: 107162
Kategorija prozivoda: Matične ploče
Proizvođač: GIGABYTE

Cena: 6.920,00



Tip procesora	AMD
Podnožje	AMD® AM4
Čipset	AMD® A520
Format ploče	Micro ATX
Podržani procesori	AMD Socket AM4, support for: AMD Ryzen™ 5000 Series/ Ryzen™ 5000 G-Series/ Ryzen™ 4000 G-Series and Ryzen™ 3000 Series Processors
Podržana memorija	DDR4
Memorija	2 x DDR4 DIMM sockets supporting up to 64 GB (32 GB single DIMM capacity) of system memorySupport for DDR4 5100(O.C.) / 4800(O.C.) / 4600(O.C.) / 4400(O.C.) / 4266(O.C.) / 4133(O.C.) / 4000(O.C.) / 3866(O.C.) / 3733(O.C.) / 3600(O.C.) / 3466(O.C) / 3400(O.C.) / 3200 / 2933 / 2667 / 2400 / 2133 MHz memory modulesDual channel memory architectureSupport for ECC Un-buffered DIMM 1Rx8/2Rx8 memory modules** ECC memory (ECC mode) support varies by CPUSupport for non-ECC Un-buffered DIMM 1Rx8/2Rx8/1Rx16 memory modulesSupport for Extreme Memory Profile (XMP) memory modules
Slotovi za proširenje	CPU:1 x PCI Express x16 slot, supporting PCIe 3.0 and running at x16Chipset:2 x PCI Express x1 slots, supporting PCIe 3.0
Storage	CPU:1 x M.2 connector (Socket 3, M key, type 2242/2260/2280 SATA and PCIe 3.0 x4/x2 SSD support)Chipset:4 x SATA 6Gb/s connectorsSupport for RAID 0, RAID 1, and RAID 10
Mrežna karta	Realtek® GbE LAN chip (1 Gbit/100 Mbit)
Zvučna karta	Realtek® Audio CODECHigh Definition Audio2/4/5.1/7.1-channel
USB	CPU:4 x USB 3.2 Gen 1 ports on the back panelChipset:2 x USB 3.2 Gen 1 ports available through the internal USB header6 x USB 2.0/1.1 ports (2 ports on the back panel, 4 ports available through the internal USB headers)
Konektori na zadnjoj strani	1 x PS/2 keyboard/mouse port1 x DVI-D port1 x HDMI port4 x USB 3.2 Gen 1 ports2 x USB 2.0/1.1 ports1 x Q-Flash Plus button1 x RJ-45 port3 x audio jacks
Interni konektori	1 x 24-pin ATX main power connector1 x 8-pin ATX 12V power connector1 x CPU fan header2 x system fan headers1 x addressable LED strip header1 x RGB LED strip header1 x M.2 Socket 3 connector4 x SATA 6Gb/s connectors1 x front panel header1 x front panel audio header1 x speaker header1 x USB 3.2 Gen 1 header2 x USB 2.0/1.1 headers1 x Trusted Platform Module (TPM) header (2x6 pin, for the GC-TPM2.0_S module only)1 x serial port header1 x chassis intrusion header1 x Clear CMOS jumper
Bios	1 x 128 Mbit flashUse of licensed AMI UEFI BIOSPnP 1.0a, DMI 2.7, WfM

Cene su informativnog karaktera. Prodavac ne odgovara za tačnost cena iskazanih na sajtu, zadržava pravo izmena cena. Ponudu za ostale artikle, informacije o stanju lagera i aktuelnim cenama možete dobiti na upit. Plaćanje se isključivo vrši virmanski - bezgotovinski.