

Tenda N301 \* Wireless N300 Ruter, WISP/univ.  
repeater/WDS-bridge/client+AP/WPS, 3L/1W  
2x5dB (1699)



Šifra: 11582

Kategorija proizvoda: Mrežna oprema

Proizvođač: TENDA

**Cena: 1.290,00**

N301 je zameski proizvod za : N150 (150N Tenda ruter) , N3 (150N Tenda ruter)

#### Hardware Features

Protocols & Standards IEEE 802.3/3U IEEE 802.11n/g/b

Interface 1 10/100Mbps WAN Port

3 10/100Mbps LAN Ports

Antenna 2 fixed 5dbi Omni Directional antennas

Button 1 Reset/WPS Button

Dimensions (L\*W\*H) mm 127.4mm\*90.5mm\*26mm

#### Wireless Features

Wireless Link Rate IEEE 802.11n: up to 300Mbps

IEEE 802.11g: up to 54Mbps

IEEE 802.11b: up to 11Mbps

Frequency Range (GHz) 2.412GHz-2.472GHz

Working Mode Universal Repeater

AP

WISP

WDS Bridge

Wireless Security 64/128bit WEP

WPA-PSK

WPA2-PSK

WPS support

Wireless Function Enable/Disable Wireless Radio

Wireless Access Control

Reception Sensitivity b mode:1M -92dBm@8% 11M -87dBm@8% PER;

g mode:54M -72dBm@8% PER;

n mode:72.2M -68dBm@8% PER; 150M -68dBm@8% PER;

#### Software Features

Internet Connection Type Dynamic IP?PPPOE?Static IP?L2TP?PPTP

DHCP Server Built-in DHCP server

DHCP Client List

Address Reservation

Virtual Server Port Forwarding

DMZ Host

Parental Control Client Filter

Mac Filter

Websites Filter

Dynamic DNS No-IP

dyndns

VPN Pass-Through PPTP

L2TP

Other Advanced Function Bandwidth Control  
Mac Address Clone  
Remote Web Management  
System Log  
Others  
Package Contents Wireless N300 Easy Setup Router N301  
Quick Installation Guide  
Ethernet cable  
Power adapter  
Resources CD  
Environment Operating Temperature: 0?~40?  
Storage Temperature: -40?~70?  
Operating Humidity: 10%~90% non-condensing  
Storage Humidity: 5%~90% non-condensing  
Certificates FCC, CE,RoHs

Nacin podesavanja UNIVERSAL REPEATER:  
<http://www.tendacn.com/en/faq/2913.html>

Tenda Mrežni wireless adapteri i ruteri adsl 3g tp-link  
##