Firma: PC COOL DOO
Adresa: Višegradska 26A
Telefon: 0653526116
Fax:
PIB: 104045201
E-mail: info@pccool.rs

Tenda AC8 AC1200 wireless dual band ruter 2.4+5GHz, 1W/3L, Gbit, 1Ghz cpu 128mb, 4x6dBi 9V/1A

Šifra: 11587
Kategorija prozivoda: Mrežna oprema
Proizvođač: TENDA

Cena: 3.890,00



AC8 is a dual band gigabit wireless router specially designed for family with fibre access.Equipped with gigabit ports to support up to 1000 Mbps bandwidth access. The dual band provide 1167Mbps frequency, fully utilise the gigabit fibre.This router is equipped with 28nm 1 GHz CPU to provide better performance. The integrated dual-band technology combines both 2.4GHz and 5GHz under one Wi-Fi name; The 5GHz frequency band is set as priority and faster signal frequency would be allocated to you automatically by our dynamic optimization system. New designed 6 dBi antennas,meet the coverage requirement for small and medium household. AC8 also support broadband account automatic transfer and other features

Standard&Protocol IEEE802.3,IEEE802.3u,IEEE802.3ab
Interface 1*10/100/1000Mbps WAN port
3*10/100/1000Mbps LAN ports
Antenna 4*6dBi external dual band antennas
Button 1*WPS/Reset button
Power Input:AC 200-240V—50/60Hz
Output: DC 9V 1A
LED indicator 1*LED
Dimension 200x127x33.6mm(L*W*H)
Wireless Standards IEEE 802.11ac/a/n @5GHz
IEEE 802.11b/g/n @2.4GHz
Data Rate2.4GHz: 300Mbps
5GHz: 867Mbps
Frequency 2.4GHz & 5GHz
Wireless Security WPA-PSK/WPA2-PSK, WPA/WPA2
Wireless Security : Enable /Disable
Internet Connection Type PPPoE, Dynamic IP, Static IP
Support automatic access detection
Supports broadband account automatic transfer
Operating Mode Wireless Router Mode
AP Mode
Universal Repeater mode
WISP Mode
DHCP DHCP Server
DHCP Client List
DHCP Reservation
Virtual Server Port Forwaring
DMZ Host
UPnP
Security Client Filter(supports black list and white list)
Parental Control(supports black list and white list)
Remote Web Management
Firewall Forbid WAN PING from internet
DDNS Support DynDNS, 88ip
Other FunctionBroadband management
MAC address clone
Static Routing
System Log
Backup & Restore configurations
Firmware upgrade from local

Temperature Operating Temperature: 0? ~ 40?
Storage Temperature: -40? ~ 70?.
Humidity Operating Humidity:10% ~ 90% RH non-condensing
Storage Humidity: 5% ~ 90%RH non-condensing.
Default Settings Default Access: tendawifi.com or http://192.168.0.1
Certification CE FCC CCC SRRC

Cene su informativnog karaktera. Prodavac ne odgovara za tačnost cena iskazanih na sajtu, zadržava pravo izmena cena. Ponudu za ostale artikle, informacije o stanju lagera i aktuelnim cenama možete dobiti na upit. Plaćanje se isključivo vrši virmanski - bezgotovinski.