

Tenda i24 WiFi access point dual band ruter
2.4+5GHz 300/867Mbps AP client, 1xL 2x4dBi
1xgbit POE

Šifra: 11588
Kategorija proizvoda: Mrežna oprema
Proizvođač: TENDA

Cena: 9.680,00



Dimension 178 × 178 × 38mm
Ethernet Interface 1 x 10/100/1000 Base TX
Antenna
2.4GHz: 2 x 4dBi
5GHz: 2 x 4dBi
Button:
1 x RESET
LED Indicator
1 x SYS
Maximum Power Consumption Power supply standard 802.3af/at and DC: 12V 1A
Wireless Frequency Band 2.4GHz
Data Rate
2.4GHz: 300Mbps
5GHz: 867Mbps
Wireless Standards 802.11a/b/g/n/ac(wave2)
Max Transmit Power
2.4GHz: 23dBm
5GHz: 23dBm
Sensitivity
802.11b :-93 dBm
2.4 GHz 802.11n (MCS7):-73dBm
5 GHz 802.11a :-93 dBm
5 GHz 802.11n (MCS7) :-74 dBm
Software
MU-MIMO
Support
Operating modes
AP.Client AP
Hide SSID
Support
Max. No. of SSID
2.4GHz: 8
5GHz: 4
Max. connected clients 256
WEP Support
WPA-PSK Support
WPA2-PSK Support
WPA Support
WPA2 Support
Access control Support
Adjustable power transmit Support

AP isolation Support
Connected clients control Support
RSSI Threshold Support
WMM Support
VLAN tagging for SSID Support
LED control Support
Diagnostics tool Support
Scheduled reboot Support
Reboot at specified interval Support
Centralized Management Support
System logs Support
Firmware upgrade Support
Reboot Support
Reset Support
Backup configuration Support
Restore configuration Support
Default login IP address 192.168.0.254
Default user name admin
Default password admin
Operating temperature -10? ~ 40?
Operating humidity 10%~90% non-condensing
Storage temperature -30? ~ 70?
Storage humidity 10%~90% non-condensing