Firma: PC COOL DOO
Adresa: Višegradska 26A
Telefon: 0653526116
Fax:
PIB: 104045201
E-mail: info@pccool.rs

Tenda AC6 AC1200 wireless dual band ruter 2.4+5GHz, 1W/3L 10/100,1Ghz cpu, 4x5dBi hi pwr 12v1a

Šifra: 11658
Kategorija prozivoda: Mrežna oprema
Proizvođač: TENDA

Cena: 3.920,00



AC6 is a Smart Dual-band WiFi Router with strong signal and stable performance. It supports 5th generation Wi-Fi standard 802.11ac and the concurent dual-band speed is up to 1167Mbps. 900MHz CPU from Broadcom offers fast & stable performance. AC6 has 2x through-wall ability than normal routers with its independent power amplifiers, beamforming+ Intelligent technology and 4x 5dBi HG antennas. You can enjoy lag-free gaming and uninterrupted video streaming anytime anywhere. Additionally, AC6 supports smart power saving technology, App remote management, creates a low-power consumption and smart eco-friendly life for your whole family.
Standard&Protocol: IEEE802.3, IEEE802.3u
Interface: 1*10/100Mbps WAN port
3*10/100Mbps LAN ports
Antenna: 4*5dBi external antennas
Button: 1*WiFi on/off, 1* Reset/WPS button
Power: Input:100-240V—50/60Hz, 0.2A
Output:DC 12V==1A
Dimension: 220*141.5*49mm
LED: System*1,WAN*1, LAN*1, 2.4G*1, 5G*1,WPS*1
Wireless Standards: IEEE 802.11ac/a/n 5GHz
IEEE 802.11b/g/n 2.4GHz
Data rate5GHz: Up to 867Mbps
2.4GHz: Up to 300Mbps
Frequency: Simultaneous dual band 2.4 & 5GHz
Transmit PowerCE:
<20dBm(2.4G)
<23dBm(5G)
FCC:
<30dBm
Basic Features: SSID Broadcast: Enable/Disable
Transmission Power: high, medium, low
Beamforming
Wireless SecurityWPA-PSK/WPA2-PSK, WPA/WPA2
Wireless Security: Enable/Disable
WPS(WiFi Protected Set-up) fast encryption
Internet Connection Type: PPPoE, Dynamic IP, Static IP
PPPoE(Russia), PPTP(Russia), L2TP(Russia)
Operating Mode:
-Wireless Router Mode
-Universal Repeater Mode
-WISP Mode
DHCP Server:
DHCP Server
DHCP Client List
DHCP Reservation
Virtual Server:
Port Forwarding
DMZ Host
UPnP
Security: Client Filter
Parental Control(support black list and white list)
Remote Web Management

Firewall: Forbid UDP flood attack
Forbid TCP flood attack
Forbid flood attack
Forbid WAN PING from internet
DDNS: Support DynDNS, No-ip, 3322.org, Oray.com, 88ip
VPNIPsec pass through
PPTP pass through
L2TP pass through
PPTP server
PPTP client
L2TP client
FeaturesSmart WiFi Schedule
Smart Power Saving
Smart LED on/off
Tenda Cloud
Tenda App
OtherBandwidth Control
Guest Network
IPTV
MAC Clone
Static Routing
System Log
Backup & Restore configurations
Firmware upgrade online
Firmware upgradeable via browser
TemperatureOperating Temperature: 0? ~ 40?
Storage Temperature: -40? ~ 70?.
HumidityOperating Humidity:10% ~ 90% RH non-condensing
Storage Humidity: 5% ~ 90%RH non-condensing.
Default SettingsDefault Access: tendawifi.com

Cene su informativnog karaktera. Prodavac ne odgovara za tačnost cena iskazanih na sajtu, zadržava pravo izmena cena. Ponudu za ostale artikle, informacije o stanju lagera i aktuelnim cenama možete dobiti na upit. Plaćanje se isključivo vrši virmanski - bezgotovinski.