

Tenda AC6 AC1200 wireless dual band ruter
2.4+5GHz, 1W/3L 10/100,1Ghz cpu, 4x5dBi hi
pwr 12v1a

Šifra: 11658
Kategorija proizvoda: Mrežna oprema
Proizvođač: TENDA

Cena: 3.920,00



AC6 is a Smart Dual-band WiFi Router with strong signal and stable performance. It supports 5th generation Wi-Fi standard 802.11ac and the concurrent dual-band speed is up to 1167Mbps. 900MHz CPU from Broadcom offers fast & stable performance. AC6 has 2x through-wall ability than normal routers with its independent power amplifiers, beamforming+ Intelligent technology and 4x 5dBi HG antennas. You can enjoy lag-free gaming and uninterrupted video streaming anytime anywhere. Additionally, AC6 supports smart power saving technology, App remote management, creates a low-power consumption and smart eco-friendly life for your whole family.

Standard&Protocol: IEEE802.3, IEEE802.3u

Interface: 1*10/100Mbps WAN port

3*10/100Mbps LAN ports

Antenna: 4*5dBi external antennas

Button: 1*WiFi on/off, 1* Reset/WPS button

Power: Input:100-240V—50/60Hz, 0.2A

Output:DC 12V==1A

Dimension: 220*141.5*49mm

LED: System*1, WAN*1, LAN*1, 2.4G*1, 5G*1, WPS*1

Wireless Standards: IEEE 802.11ac/a/n 5GHz

IEEE 802.11b/g/n 2.4GHz

Data rate 5GHz: Up to 867Mbps

2.4GHz: Up to 300Mbps

Frequency: Simultaneous dual band 2.4 & 5GHz

Transmit Power CE:

FCC:

Basic Features: SSID Broadcast: Enable/Disable

Transmission Power: high, medium, low

Beamforming

Wireless Security WPA-PSK/WPA2-PSK, WPA/WPA2

Wireless Security: Enable/Disable

WPS(WiFi Protected Set-up) fast encryption

Internet Connection Type: PPPoE, Dynamic IP, Static IP

PPPoE(Russia), PPTP(Russia), L2TP(Russia)

Operating Mode:

-Wireless Router Mode

-Universal Repeater Mode

-WISP Mode

DHCP Server:

DHCP Server

DHCP Client List

DHCP Reservation

Virtual Server:

Port Forwarding

DMZ Host
UPnP
Security: Client Filter
Parental Control(support black list and white list)
Remote Web Management
Firewall: Forbid UDP flood attack
Forbid TCP flood attack
Forbid flood attack
Forbid WAN PING from internet
DDNS: Support DynDNS, No-ip, 3322.org, Oray.com, 88ip
VPNIPsec pass through
PPTP pass through
L2TP pass through
PPTP server
PPTP client
L2TP client
FeaturesSmart WiFi Schedule
Smart Power Saving
Smart LED on/off
Tenda Cloud
Tenda App
OtherBandwidth Control
Guest Network
IPTV
MAC Clone
Static Routing
System Log
Backup & Restore configurations
Firmware upgrade online
Firmware upgradeable via browser
TemperatureOperating Temperature: 0? ~ 40?
Storage Temperature: -40? ~ 70?.
HumidityOperating Humidity:10% ~ 90% RH non-condensing
Storage Humidity: 5% ~ 90%RH non-condensing.
Default SettingsDefault Access: tendawifi.com
Package ContentAC1200 Smart Dual-Band WiFi Router
Power Adapter
Install Guide
Ethernet Cable