Firma: PC COOL DOO
Adresa: Višegradska 26A
Telefon: 0653526116
Fax:
PIB: 104045201
E-mail: info@pccool.rs

Tenda AC5 AC1200 wireless dual band ruter 2.4+5GHz, 1W/3L 10/100, 1Ghz cpu, 4x5dBi , 9v/1a

Šifra: 11672
Kategorija prozivoda: Mrežna oprema
Proizvođač: TENDA

Cena: 3.070,00



FIRMWARE 11.8.2020 to prevent backdoor hacking if using remote control function: https://www.tendacn.com/en/download/detail-3193.html

AC5 AC1200 Smart Dual-Band WiFi Router.Migration of ISP User Name and Password, Four 5dBi dual-band omni-directional antennas,1 GHz CPU / MU-MIMO / Beamforming+ technology, Remote management via Tenda WiFi App.Equipped with a 1 GHz high-frequency CPU made with 28nm process, AC5 outperforms ordinary routers. Stable and fast internet connection lets you enjoy smooth 4K HD videos and online games without delay.

Standard&Protocol IEEE802.3, IEEE802.3u
Interface 10/100 Mbps WAN port*1
10/100 Mbps LAN port*3
Antenna 5dBi External antenna*4
Button WPS/Reset button*1, WiFi on/off button*1
Power AC input: 100-240V-50/60Hz, 0.2A
DC output: 9V 1A
LED indicator System*1, WiFi*1, WAN*1, LAN*3
Data Rate 5 GHz: Up to 867 Mbps
2.4 GHz: Up to 300 Mbps
Frequency Concurrent dual band 2.4 GHz & 5 GHz
Transmit Power2.4G:
16dbm@MCS7
17dbm@OFDM 54M
19dbm@CCK 11M
5G:
12dbm@MCS9
14dbm@MCS7
Basic Features SSID Broadcast: Enable/Disable
Beamforming
MU-MIMO
Wireless Security WPA-PSK/WPA2-PSK, WPA/WPA2
Wireless Security: Enable/Disable
WPS (WiFi Protected Set-up) quick encryption
Internet Connection Type PPPoE, Dynamic IP, Static IP
PPPoE (Russia), PPTP (Russia), L2TP (Russia)
Operating mode Wireless Router Mode
Universal Repeater Mode
WISP Mode
AP Mode
DHCP Server DHCP Server
DHCP Client List
DHCP Reservation
Virtual Server Port Forwarding
DMZ Host
UPnP
Security Client Filter (support blacklist and whitelist)
Parental Control
Remote Management
Firewall Forbid UDP flood attack

Forbid TCP flood attack
Forbid flood attack
Forbid WAN PING from internet
DDNS Support DDNS, No-ip, 3322.org, Oray.com, 88ip
VPNIpsec
PPTP
L2TP
PPTP client
L2TP client
Features PPPoE Username/Password Clone
Smart WiFi Schedule
Smart Sleeping Mode
Smart LED on/off
Tenda WiFi App
Other Bandwidth Control
Guest Network
IPTV
MAC Address Clone
Static Routing
System Log
Backup & Restore configurations
Online firmware upgrade
Local firmware upgrade
Temperature Operating Temperature: 0? - 40?
Storage Temperature: -40? -70?.
Humidity Operating Humidity: (10 - 90)% RH non-condensing
Storage Humidity: (5 - 90%) RH non-condensing.
Default Settings Default Access: tendawifi.com
Certification CE/FCC/RoHS

Cene su informativnog karaktera. Prodavac ne odgovara za tačnost cena iskazanih na sajtu, zadržava pravo izmena cena. Ponudu za ostale artikle, informacije o stanju lagera i aktuelnim cenama možete dobiti na upit. Plaćanje se isključivo vrši virmanski - bezgotovinski.