Firma: PC COOL DOO
Adresa: Višegradska 26A
Telefon: 0653526116
Fax:
PIB: 104045201
E-mail: info@pccool.rs

Tenda AC5 v3 AC1200 wireless dual band ruter 2.4+5GHz, 1W/3L 10/100, 1Ghz cpu, 4x5dBi ,9v/1

Šifra: 11694
Kategorija prozivoda: Mrežna oprema
Proizvođač: TENDA

Cena: 2.830,00



FIRMWARE 11.8.2020 to prevent backdoor hacking if using remote control function: https://www.tendacn.com/en/download/detail-3193.html

AC5 is an AC1200 dual band WiFi router, designed for medium-sized apartment with a 100Mbps fiber access. It provides WiFi speed up to 1167 Mbps (5GHz: 867Mbps and 2.4GHz: 300Mbps). Adopted the integrated dual-band technology, combining 2.4GHz and 5GHz signals under one WiFi name. The faster band would be allocated to your devices automatically by our dynamic optimization system. Meanwhile, featured with 4*6dBi high-gain antennas and equipped with a 28nm high performance CPU, it brings a better internet experience. AC5 supports IPv6 protocol, it can reduce the data transmission time and minimize the lag. Furthermore, the remote management function by the Tenda WiFi App provides the easiest way to manage AC5.
Standard&Protocol IEEE802.3,IEEE802.3u,IEEE802.3ab
Interface 1*10/100Mbps WAN port
3*10/100Mbps LAN ports
Antenna 4*6dBi external high-gain antennas
Button 1*WPS/Reset button
Power Input:AC 100-240V—50/60Hz
Output:DC 9V 1A
LED indicator 1*LED
Dimension 200x127x33.6mm(L*W*H)
Wireless Standards IEEE 802.11ac/a/n @5GHz
IEEE 802.11b/g/n @2.4GHz
Data Rate 2.4GHz: 300Mbps
5GHz: 867Mbps
Frequency 2.400 – 2.4835 GHz
5.150 – 5.250 GHz
Wireless Security WPA-PSK/WPA2-PSK, WPA/WPA2
Wireless Security : Enable /Disable
Internet Connection Type PPPoE, Dynamic IP, Static IP
Support automatic access detection
Supports broadband account automatic transfer
Operating Mode Wireless Router Mode
AP Mode
Universal Repeater mode
WISP Mode
DHCP DHCP Server
DHCP Client List
DHCP Reservation
Virtual ServerPort Forwaring
DMZ Host
UPnP
Security Client Filter(supports black list and white list)
Parental Control(supports black list and white list)
Remote Web Management
Firewall Forbid WAN PING from internet
DDNS Support DynDNS, 88ip
Other featuresSupport IPv6
Broadband management
MAC address clone

Static Routing
System Log
Backup & Restore configurations
Firmware upgrade from local
Temperature Operating Temperature: 0? ~ 40?
Storage Temperature: -40? ~ 70?.
Humidity Operating Humidity:10% ~ 90% RH non-condensing
Storage Humidity: 5% ~ 90%RH non-condensing.
Default SettingsDefault Access: tendawifi.com or http://192.168.0.1
Certification CE,RoHS,FCC,CCC,SRRC,
EIRP Power (Max.)2.400 – 2.4835 GHz:19.85 dBm (EIRP)
5.150 – 5.250 GHz:22.96dBm (EIRP)

Cene su informativnog karaktera. Prodavac ne odgovara za tačnost cena iskazanih na sajtu, zadržava pravo izmena cena. Ponudu za ostale artikle, informacije o stanju lagera i aktuelnim cenama možete dobiti na upit. Plaćanje se isključivo vrši virmanski - bezgotovinski.