Firma: PC COOL DOO
Adresa: Višegradska 26A
Telefon: 0653526116
Fax:
PIB: 104045201
E-mail: info@pccool.rs

Tenda AC10 * V3.0 AC1200 wireless dual band ruter 2.4+5GHz, 1W/3L, Gbit, 1Ghz cpu 128mb,4x6dBi 3299

Šifra: 11698
Kategorija prozivoda: Mrežna oprema
Proizvođač: TENDA

Cena: 2.650,00



AC10 offers dual-band Gigabit wireless with all-new 802.11ac Wave 2.0 standard. Its powerful 1GHz CPU provide the best performance in both 2.4GHz and 5GHz. The 5GHz band works at up to 867Mbps, while the 2.4GHz frequency tops 300Mbps, serving an incredible combined bandwidth of 1167Mbps.With 1 GHz CPU made with 28 nm process, AC10 manifests excellent capacity on data processing and energy conservation. It works well with optical fiber with bandwidth ranging from 50 M, 100 M, 200 M to even 1000 M, allowing you to enjoy smooth HD videos and games.

Standard&Protocol IEEE802.3, IEEE802.3u, IEEE802.3ab
Interface
1*10/100/1000Mbps WAN port
3*10/100/1000Mbps LAN ports
Antenna 4*6dBi external antennas
Button 1*WPS/Reset button
Power Input:AC 100-240V~50/60Hz, 0.4A
Output:DC 9V?1A
Dimension 8.66 * 5.57 * 1.93 in (220*141.5*49mm)(W*D*H)
LED indicator Sys*1,WAN*1, LAN*1,WiFi/WPS*1
Wireless StandardsIEEE 802.11ac wave2/a/n 5GHz
IEEE 802.11b/g/n 2.4GHz
Data Rate5GHz: Up to 867Mbps
2.4GHz: Up to 300Mbps
Frequency Simultaneous dual band 2.4 & 5GHz
Transmit PowerCE:
<20dBm(2.4G)
<23dBm(5G)
FCC:<30dBm
Basic Features SSID Broadcast: Enable/Disable
Transmission Power: high, medium, low
Beamforming
MU-MIMO
Wireless Security WPA-PSK/WPA2-PSK, WPA/WPA2
Wireless Security : Enable /Disable
Internet Connection TypePPPoE, Dynamic IP, Static IP
Support automatic access detection
Supports broadband account automatic transfer
Operating ModeWireless Router Mode
AP Mode
Universal Repeater mode
WISP Mode
DHCP ServerDHCP Server
DHCP Client List
DHCP Reservation
Virtual ServerPort Forwaring
DMZ Host
UPnP
SecurityClient Filter(supports black list and white list)
Parental Control(supports black list and white list)
Remote Web Management
FirewallForbid UDP flood attack

Forbid TCP flood attack
Forbid flood attack
Forbid WAN PING from internet
DDNSSupport DynDNS, 88ip
VPNIPsec pass through
PPTP pass through
L2TP pass through
Special Features PPPoE Username/password Clone Smart WiFi Schedule
Smart Power Saving
Smart LED on/off
Tenda Cloud
Tenda App
Software Other Broadband management MAC address clone
Static Routing
System Log
Backup & Restore configurations
Firmware upgrade from local
Temperature Operating Temperature: 0? ~ 40?
Storage Temperature: -40? ~ 70?.
Humidity Operating Humidity:10% ~ 90% RH non-condensing
Storage Humidity: 5% ~ 90%RH non-condensing.
Default SettingsDefault Access: tendawifi.com or
http://192.168.0.1
CertificationCE/FCC/RoHS
EIRP Power (Max.)2.400-2.4835GHz: 19.95dBm (EIRP)
5.150-5.250GHz: 22.90dBm (EIRP)
Package Content

Cene su informativnog karaktera. Prodavac ne odgovara za tačnost cena iskazanih na sajtu, zadržava pravo izmena cena. Ponudu za ostale artikle, informacije o stanju lagera i aktuelnim cenama možete dobiti na upit. Plaćanje se isključivo vrši virmanski - bezgotovinski.