

Tenda AC10 * V3.0 AC1200 wireless dual band
 ruter 2.4+5GHz, 1W/3L, Gbit, 1Ghz cpu
 128mb,4x6dBi 3299

Šifra: 11698
 Kategorija proizvoda: Mrežna oprema
 Proizvođač: TENDA

Cena: 2.650,00



AC10 offers dual-band Gigabit wireless with all-new 802.11ac Wave 2.0 standard. Its powerful 1GHz CPU provide the best performance in both 2.4GHz and 5GHz. The 5GHz band works at up to 867Mbps, while the 2.4GHz frequency tops 300Mbps, serving an incredible combined bandwidth of 1167Mbps. With 1 GHz CPU made with 28 nm process, AC10 manifests excellent capacity on data processing and energy conservation. It works well with optical fiber with bandwidth ranging from 50 M, 100 M, 200 M to even 1000 M, allowing you to enjoy smooth HD videos and games.

Standard&Protocol IEEE802.3, IEEE802.3u, IEEE802.3ab
 Interface

1*10/100/1000Mbps WAN port

3*10/100/1000Mbps LAN ports

Antenna 4*6dBi external antennas

Button 1*WPS/Reset button

Power Input:AC 100-240V~50/60Hz, 0.4A

Output:DC 9V?1A

Dimension 8.66 * 5.57 * 1.93 in (220*141.5*49mm)(W*D*H)

LED indicator Sys*1, WAN*1, LAN*1, WiFi/WPS*1

Wireless Standards IEEE 802.11ac wave2/a/n 5GHz

IEEE 802.11b/g/n 2.4GHz

Data Rate 5GHz: Up to 867Mbps

2.4GHz: Up to 300Mbps

Frequency Simultaneous dual band 2.4 & 5GHz

Transmit Power CE:

FCC: Basic Features SSID Broadcast: Enable/Disable

Transmission Power: high, medium, low

Beamforming

MU-MIMO

Wireless Security WPA-PSK/WPA2-PSK, WPA/WPA2

Wireless Security : Enable /Disable

Internet Connection Type PPPoE, Dynamic IP, Static IP

Support automatic access detection

Supports broadband account automatic transfer

Operating Mode Wireless Router Mode

AP Mode

Universal Repeater mode

WISP Mode

DHCP Server DHCP Server

DHCP Client List

DHCP Reservation

Virtual Server Port Forwarding

DMZ Host

UPnP
SecurityClient Filter(supports black list and white list)
Parental Control(supports black list and white list)
Remote Web Management
FirewallForbid UDP flood attack
Forbid TCP flood attack
Forbid flood attack
Forbid WAN PING from internet
DDNSSupport DynDNS, 88ip
VPNIPsec pass through
PPTP pass through
L2TP pass through
Special Features PPPoE Username/password Clone Smart WiFi Schedule
Smart Power Saving
Smart LED on/off
Tenda Cloud
Tenda App
Software Other Broadband management MAC address clone
Static Routing
System Log
Backup & Restore configurations
Firmware upgrade from local
Temperature Operating Temperature: 0? ~ 40?
Storage Temperature: -40? ~ 70?
Humidity Operating Humidity:10% ~ 90% RH non-condensing
Storage Humidity: 5% ~ 90%RH non-condensing.
Default SettingsDefault Access: tendawifi.com or
http://192.168.0.1
CertificationCE/FCC/RoHS
EIRP Power (Max.)2.400-2.4835GHz: 19.95dBm (EIRP)
5.150-5.250GHz: 22.90dBm (EIRP)
Package Content
Wireless Router*1
Gigabit Ethernet Cable*1
Power Adapter*1
Installation Guide*1