Firma: PC COOL DOO
Adresa: Višegradska 26A
Telefon: 0653526116
Fax:
PIB: 104045201
E-mail: info@pccool.rs

Tenda TEF1109TP-8-102W LAN 8-Port 10/100 Base-TX(Data/Power) +1Base-TX(Data) Ethernet ports Switch

Šifra: 11708
Kategorija prozivoda: Mrežna oprema
Proizvođač: TENDA

Cena: 9.290,00



The Gigabit Uplink Port To Guarantee the Transmission Smooth and Stable It provides 8 10/100M RJ45 ports and 1 gigabit port. By using CAT5e twisted pairs, it can provide power and data transmission to APs, IP cameras, IP phones, and so on, fully loaded

Transmission Distance up to 250m
With the extension technology,data can be transmitted through 250 meters cable which would be a cost-effective replacement for extenders and optical fibers.

Excellent Lightning Protection
The switch supports 6 kV lightning protection for uplink port, protecting the switch from thunderstorms and making it more stable.

What's Special for TEF1109TP-8-102W :
Simple Port VLAN Setup
With VLAN Mode on , ports 1 to 8 are isolated from each other, enabling the switch to isolate broadcast storm, improving LAN security and data transmission.

Network standards IEEE 802.3? IEEE 802.3u?IEEE 802.3x?IEEE 802.3af?IEEE 802.3at
LED indicators:
9* Link/Ack LED indicators
1 * Power LED indicator
Interfaces:
8*10/100 Base-TX Ethernet ports (Data/Power)
1*10/100 Base-TX Ethernet ports (Data)
Transmission media
Recommended: CAT5/5e UTP or better
Fan quantity N/A
Dimensions(L*W*H) 177.5mmx104.0mmx26.0mm
Level of protection:
Lightning protection for ports: 6KV
Lightning protection for power: 6KV
ESD:
Air discharge: ±10kV
Contact discharge: ±8kV
Forwarding mode
Store-and-forward
Switch capacity 2.6 Gbps
Packet forwarding rate 1.34Mpps
Buffer 1.25Mb
MAC address table 2K
Jombo frame N/A
PoE budget
Single port: AF: 15.4W, AT: 30W
Whole device: 92W
Power consumption /
Input voltage
100-240V AC 50/60Hz
51V /2A DC(Power Adapter)
Mounting
Desktop mounting: support
Wall mounting: support

Rack mounting : non-support
Environment
Operating Temperature: 0?~45?
Storage Temperature: -40?~70?
Operating Humidity: 10%~90% non-condensing Storage Humidity: 5%~90% non-condensing
Certificates
FCC?CE?RoHS
Software
Function
Default Mode: If Default mode is enabled, the device works as a general switch and all ports

Cene su informativnog karaktera. Prodavac ne odgovara za tačnost cena iskazanih na sajtu, zadržava pravo izmena cena. Ponudu za ostale artikle, informacije o stanju lagera i aktuelnim cenama možete dobiti na upit. Plaćanje se isključivo vrši virmanski - bezgotovinski.