Firma: PC COOL DOO
Adresa: Višegradska 26A
Telefon: 0653526116
Fax:
PIB: 104045201
E-mail: info@pccool.rs

IP-COM F1109DT LAN 9-Port 10/100 Switch RJ45 ports (1xgigabit port) (alt=TEF1109DT)



Šifra: 11713
Kategorija prozivoda: Mrežna oprema
Proizvođač: IP-COM

Cena: 2.090,00

8FE+1GE Ethernet Umanaged Switch
Compliant with IEEE802.3, IEEE802.3u, IEEE802.3x, IEEE802.3ab standards.
8*10/100Mbps and 1*10/100/1000 Mbps auto-negotiation ports.
2K MAC address ,MAC auto Learning & auto Aging.
Auto MDI/MDIX.
IEEE 802.3x full duplex flow control, and backpressure half duplex flow control.
Offers 6 kV lightning protection for its uplink port.
Support DC 9 ~ 12V power input.
Support port VLAN mode.
Support network surveillance camera access,and prevent loss of monitoring images.
Plug and play.

F1109DT is a 9-port Ethernet Umanaged Switch developed by IP-COM.It provides 1*10/100/1000 Mbps uplink port and 8*10/100 Mbps RJ45 ports. Equipped with large packet buffer, it also ensures smooth streaming even when 8 HD IP cameras are working simultaneously. You can enable port VLAN mode of the switch to protect your LAN network from broadcast storm and prevent loss of monitoring images. In addition, the switch offers 6 kV lightning protection for its uplink port. In a word, F1109DT can provide economical solutions for small and medium-sized IP surveillance projects and enterprises.
Enjoy Super HD Video Screen
Equipped with 1024 KB large packet buffer,it ensures smooth streaming even when eight HD IP cameras of 500W are working simultaneously.

Excellent Lightning Protection
The switch supports 6 kV lightning protection for uplink port,protecting the switch from thunderstorms and making it more stable.

Transmission Distance up to 250m
With the extension technology,data can be transmitted through 250 meters cable which would be a cost-effective replacement for extenders and optical fibers.

Easy Port VLAN Setup
With VLAN Mode on , ports 1 to 8 are isolated from each other, enabling the switch to isolate broadcast storm, improving LAN security and data transmission.

Model F1109DT
Standard IEEE 802.3, IEEE 802.3u, IEEE 802.3x, IEEE 802.3ab
Port 8 * 10/100 Mbps RJ45 port
1 * 10/100/1000 Mbps uplink port
Transmission media Recommended: CAT5/5e UTP or better
Forwarding rate 10 Mbps: 14880 pps
100 Mbps: 148800 pps
1000 Mbps: 1488000 pps
Power Input: 100 - 240 V AC, 50/60 Hz
Output: DC 9 - 12 V
Lightning protection 6 kV for uplink port
Dimension 140 mm * 66.5 mm * 25.3 mm(L * W * H)
LED indicato 1 * Power
9 * Link/Act
Switching capacity 3.6 Gbps
MAC address table 2 K
Power consumption Max: 5 W
Software

Store-and-forward Supported
Protocol CDMA/CD
MAC address learning Auto learning & auto aging
VLAN Supported. Port 9 is an uplink port and ports 1 to 8 are isolated from each other.
Others
Temperature Operating temperature: (0 - 40)°C
Storage temperature: (-40 - 70)°C

Cene su informativnog karaktera. Prodavac ne odgovara za tačnost cena iskazanih na sajtu, zadržava pravo izmena cena. Ponudu za ostale artikle, informacije o stanju lagera i aktuelnim cenama možete dobiti na upit. Plaćanje se isključivo vrši virmanski - bezgotovinski.