Firma: PC COOL DOO
Adresa: Višegradska 26A
Telefon: 0653526116
Fax:
PIB: 104045201
E-mail: info@pccool.rs

Netis WF2409E Wireless N300 Ruter1Ghz CPU,1W/4L, 2x5dB Repeater/AP+ WDS/WDS/Client/Multi-SSID, Wisp

Šifra: 15316
Kategorija prozivoda: Mrežna oprema
Proizvođač: NETIS

Cena: 2.120,00



The netis router

WF2409E offers 300Mbps high speed to connect your computers, smartphones, wireless cameras and other Wi-Fi devices. Bundled with three 5dBi high gain antennas, it ensures a better wireless coverage and allows you to enjoy the wireless freedom anywhere around your home, ideal for faster downloading, Internet calling and HD video streaming.

Incredible wireless high speed up to 300Mbps, great for faster downloading, Internet calling and HD video streaming
MIMO high gain 5dBi antennas providing maximum range and stable connections
Dual operation modes- Router, Bridge (pure access point)
Various WAN connection types in AP Router mode- DHCP, Static IP, PPPoE, L2TP, PPTP, Dual Access, WISP
Multiple wireless modes- AP, Repeater, AP+WDS, WDS, Client
Multi-SSID providing up to 3 additional separate networks for guests and friends
Easy wireless security setup at a push of the WPS button
Intelligent bandwidth control to manage the bandwidth usage for each computer reasonably
Internet Access Control- IP filtering, MAC Filtering, Domain Filtering based on time
Quick setup, with built-in multilingual management page

Standards IEEE 802.11b, IEEE 802.11g, IEEE 802.11n
Signal Rate Up to 300Mbps
Frequency Range 2.4-2.4835GHz
Transmit Power 20dBm(MAX)
Data Transfer Rates:
802.11n:
40MHz (300Mbps, 270Mbps, 240Mbps, 180Mbps, 120Mbps, 90Mbps, 60Mbps, 30Mbps)
20MHz (144Mbps, 130Mbps, 115Mbps, 86Mbps, 57Mbps, 43Mbps, 28Mbps, 14Mbps) (Auto-Sense)
802.11g:
(54Mbps, 48Mbps, 36Mbps, 24Mbps, 18Mbps, 12Mbps, 11Mbps, 9Mbps, 6Mbps)
802.11b:
(11Mbps, 9Mbps, 6Mbps, 5.5Mbps, 2Mbps, 1Mbps)
Wireless Modes: AP, Repeater, AP+WDS, WDS, Client, Multi-SSID
Wireless Security
64/128-bit WEP,
WPA-PSK/WPA2-PSK (TKIP/AES)
SSID Broadcast Enable/Disable
Wireless MAC Filtering

Hardware
Standards IEEE 802.3 10Base-T, IEEE 802.3u 100Base-TX
Interfaces 1 * 10/100Mbps Auto MDI/MDIX RJ45 WAN port
4 * 10/100Mbps Auto MDI/MDIX RJ45 LAN port
LED Indicators PWR, WLAN, LAN1-LAN4, WAN, WPS
Buttons WPS, Default
Antennas 3* 5dBi Fixed Antenna
Power Supply DC 9V/500mA (Output)

Software
WAN Type DHCP, Static IP, PPPoE, L2TP, PPTP, Dual Access, WISP
Port Forwarding Virtual Servers, Port Triggering, UPnP, DMZ, FTP Private Port

QoS WMM, Bandwidth Control
Access Control IP/MAC/Domain Filtering
VPN Pass-through PPTP, L2TP, IPSec
Others IPTV, Dynamic DNS, Static Routing, WOL, Backup & Restore, Firmware Upgrade
Crtification FCC, CE
Environment
Operating Temperature: 0?~40?
Storage Temperature: -40?~70?
Operating Humidity: 10%~90% non-condensing
Storage Humidity: 5%~90% non-condensing
Package

Cene su informativnog karaktera. Prodavac ne odgovara za tačnost cena iskazanih na sajtu, zadržava pravo izmena cena. Ponudu za ostale artikle, informacije o stanju lagera i aktuelnim cenama možete dobiti na upit. Plaćanje se isključivo vrši virmanski - bezgotovinski.