

Cudy MF4 4G LTE Mobile Wireless-N, Cat.4, LTE-FDD/LTE-TDD/DC-HSPA+/HSPA/UMTS, 2020mAh battery

Šifra: 15323
Kategorija proizvoda: Mrežna oprema
Proizvođač: CUDY

Cena: 5.340,00



4G LTE Mobile Wi-Fi, Model: MF4

- Share 4G connection with up to 150 Mbps download/50 Mbps upload speeds
- Support FDD and TDD bands
- Supports up to 11 devices simultaneously (10 Wireless+1 Wired)
- 2000 mAh battery for 8 hours of usage

Specifications

Model 4G LTE Mobile Wi-Fi

Dimensions 97 x 61 x 15.5mm

Weight 92g

Form MiFi / Pocket Router

Communication

System (WAN) Chipset Qualcomm MDM9x07 / MDM9x25

Frequency Bands LTE B1/B3/B7/B8/B20/B38/B40/B41

UMTS B1/B3/B8

Bandwidth LTE Band 1.4/3/5/10/15/20 MHz

Modulation Downlink QPSK/16-QAM/64-QAM

Uplink QPSK/16-QAM

Antenna Primary Internal

Diversity Internal, UMTS Optional

RF Power Level LTE FDD Power Class 3 (23 +/-2dBm)

UMTS Power Class 3 (24 +1.7/-3.7dBm)

EDGE Power Class E2 (GSM850/900: 27dBm; DCS/PCS: 26dBm)

Data Rate 4G 3GPP R10, Cat. 4, Downlink/Uplink up to 150Mbps/50Mbps

3G 3GPP R7 Downlink/Uplink up to 42Mbps/5.76Mbps

WLAN Wi-Fi Chipset RealTek 8192ES

Frequency 2.4GHz

Protocol 802.11b/g/n

Channel 1~13

Antenna Internal

Data Rate 802.11b Up to 11 Mbps

802.11g Up to 54 Mbps

802.11n Up to 150 Mbps

Feature Interface USB USB2.0

USIM Single, 4FF

LED POWER Power/Battery Status Indicator

Network 4G/3G/2G Network Status Indicator

Wi-Fi Wi-Fi Status Indicator

WebUI System Connection Status

Statistics

Samba (optional)

Device Management
Power Mangement
Mobile
Service Automatic APN matching according to USIM
Auto Data Connection
USSD Service
PIN/PUK Management
Network Mode Selection(2G/3G/LTE/Auto)
Router USB RNDIS Device
Up to 10 Wi-Fi users/devices
DHCP Server
IPv4/v6
VPN Passthrough
Firewall
WPS
Security via WEP, WPA-PSK, WPA2-PSK
Wi-Fi Settings
Battery Type Li-ion Polymer Battery
Capacity 2000mAh
Endurance 5-6 hours (normal network situation)
Operation System Windows XP/7/8/10
MAC OS 10.7+
Linux Ubuntu 13.04+
Browser IE9+, Firefox, Google Chrome, Safari, Opera
Environment Power Supply USB, 5V1A
Working Temperature 0°C to 35°C
Storage Temperature -20°C to 60°C
Certification 3GPP Compliance CE/FCC/GCF, upon customer's requirement
Meterial RoHS