

Netis W1 Wireless N300 Ruter, 1W/2L IPTV,
2x5dB AP/Repeater/AP+WDS/WDS/Client/Multi-
SSID, WISP

Šifra: 15334

Kategorija proizvoda: Mrežna oprema

Proizvođač: NETIS

Cena: 1.910,00



300Mbps Wireless N Router

The netis router W1 offers 300Mbps high speed to connect your computers, smartphones, wireless cameras and other Wi-Fi devices. Bundled with two 5dBi high gain antennas, it ensures a better wireless coverage and allows you to enjoy the wireless freedom anywhere around your home, ideal for faster downloading, Internet calling and HD video streaming.

Incredible wireless high speed up to 300Mbps, great for faster downloading, Internet calling and HD video streaming

MIMO high gain 5dBi antennas providing maximum range and stable connections

Dual operation modes- Router, Bridge (pure access point)

Various WAN connection types in AP Router mode- DHCP, Static IP, PPPoE, L2TP, PPTP, Dual Access, WISP

Multiple wireless modes- AP, Repeater, AP+WDS, WDS, Client

Multi-SSID providing up to 3 additional separate networks for guests and friends

Easy wireless security setup at a push of the WPS button

Intelligent bandwidth control to manage the bandwidth usage for each computer reasonably

Internet Access Control- IP filtering, MAC Filtering, Domain Filtering based on time

Quick setup, with built-in multilingual management page

Wireless

Standards IEEE 802.11b, IEEE 802.11g, IEEE 802.11n

Signal Rate Up to 300Mbps

Frequency Range 2.4-2.4835GHz

Transmit Power 20dBm(MAX)

Data Transfer Rate 802.11n:

40MHz (300Mbps, 270Mbps, 240Mbps, 180Mbps, 120Mbps, 90Mbps, 60Mbps, 30Mbps)

20MHz (144Mbps, 130Mbps, 115Mbps, 86Mbps, 57Mbps, 43Mbps, 28Mbps, 14Mbps) (Auto-Sense)

801.11g:

(54Mbps, 48Mbps, 36Mbps, 24Mbps, 18Mbps, 12Mbps, 11Mbps, 9Mbps, 6Mbps)

802.11b:

(11Mbps, 9Mbps, 6Mbps, 5.5Mbps, 2Mbps, 1Mbps)

Wireless Mode AP, Repeater, AP+WDS, WDS, Client, Multi-SSID

Wireless Security 64/128-bit WEP,

WPA-PSK/WPA2-PSK (TKIP/AES)

SSID Broadcast Enable/Disable

Wireless MAC Filtering

Hardware

Standards IEEE 802.3 10Base-T, IEEE 802.3u 100Base-TX

Interface 1 * 10/100Mbps Auto MDI/MDIX RJ45 WAN port

2 * 10/100Mbps Auto MDI/MDIX RJ45 LAN port

LED PWR, WLAN, LAN1-LAN4, WAN, WPS

Button WPS, Default

Antenna 2* 5dBi Fixed Antenna

Power Supply DC 9V/500mA (Output)

Software

WAN Type DHCP, Static IP, PPPoE, L2TP, PPTP, Dual Access, WISP

Port Forwarding Virtual Servers, Port Triggering, UPnP, DMZ, FTP Private Port

QoS WMM, Bandwidth Control

Access Control IP/MAC/Domain Filtering

VPN Pass-through PPTP, L2TP, IPSec

Others IPTV, Dynamic DNS, Static Routing, WOL, Backup & Restore, Firmware Upgrade

Others

Certification FCC, CE

Environment Operating Temperature: 0?~40?

Storage Temperature: -40?~70?

Operating Humidity: 10%~90% non-condensing

Storage Humidity: 5%~90% non-condensing

Package 1* W1

1* 9V/500mA Power Adapter

1* Quick Installation Guide (Multilingual)