

IP-COM F1024 LAN 24-Port 10/100M Base-T Ethernet ports Desktop or rack mount switch (alt=TEF1024D)



Šifra: 15390

Kategorija proizvoda: Mrežna oprema

Proizvođač: IP-COM

Cena: 5.190,00

24-Port Fast Ethernet Rackmount Switch

Compliant with IEEE802.3 10BASE-T, IEEE802.3u 100BASE-TX standard

Support 8K MAC address list, MAC address learning and auto-ageing

Built-in 2.5Mb SRAM (1.75Mb for packet buffer) to ensure the accuracy of data packet

6000V Lightning protection for power supply

F1024 provides 24 10/100Mbps autosensing ports and all ports support Auto MDI/MDIX for parallelwire and crosswire, making this device not only can be connection to common terminal equipments, but also can be cascade connection to other networking equipments to extend your networking easily.F1024 can provide you a easy, economic, high-performance solution for 100M networking, which is your ideal chioce for high-speed networking.

Features

? Compliant with IEEE802.3, IEEE802.3u, IEEE802.3x

? Provide 24 10/100Mbps auto-negotiation ports

? Store & forward, share memory, non-blocking architecture

? Supports MAC address self-learning and auto MDI/MDIX

? Supports full-duplex 802.3x flow control and half-duplex backpressure flow control

? Support 8K MAC address list, MAC address learning and auto-ageing

? Built-in switching power adapter, support AC 110-240V 50/60Hz input

? 6000V Lightning protection for power supply

? Fanless design

? Standard 19-inch rack-mountable, 1U steel case

? Plug and play, no need configuration

Description 24-Port Fast Ethernet Rackmount Switch

Stardand IEEE 802.3?IEEE 802.3u?IEEE 802.3x

Transmission medium UTP CAT3 or super for 10Base-T(UTP CAT5 for 100Base-T(CAT 5e(Port and module 24 FE RJ45 Ports

Backplane bandwidth 4.8Gbps

Packet forwarding rate 3.57Mpps

MAC address entries 8K

Lightning protection 6000V for power supply

Dimension 440*178*44mm(L*W*H)

Indicators Power, Link/Act

Power supply AC 100V-240V ~0.3A 50/60Hz

Power consumption MAX 5.2W(220V/50Hz)

Tenda