

x-Kamera Dahua IPC-HFW1320S-W-0280 3Mpix,
2,8mm, IP kamera, antivandal metalno kuciste

Šifra: 15875

Kategorija proizvoda: IP kamere, IP mrežni snimači

Proizvođač: Nepoznati

Cena: 5.250,00



IP kamera se koristi za video nadzor stanova, prodavnica, kancelarija itd. Povezuje se putem wi-fi ili UTP kabla. Ima rezoluciju 1080p i ugrađene IC LED diode za noćni režim. Kompatibilan je sa operativnim sistemima Android, iOS i Vindovs. Kamera je vodootporna, kućište ima klasu otpornosti IP67.

Power Supply: 12 V

Mechanical ICR filter

Easy4ip cloud support

Image converter: CMOS 1/3" with progressive scan function

Resolution: 3 Mpx

Number of pixels: 2304 x 1536

Scanning system: progressive

Electronic shutter speed: Auto / manual, from 1/3(4) sec. to 1/100000 s

Min. illumination: 0.1 Lux / F2 (color), 0lux / F2 (the IR is on)

The signal-to-noise ratio: more than 50dB

Range of IR LEDs: up to 30m

Day / night: auto (ICR) / color / black and white

Background compensation: BLC / HLC / DWDR

White balance: automatic / manual

Gain control: auto / manual

Noise reduction: 3D

Privacy zones: up to 4 zones

Focal length: 2.8 mm

Aperture: F2 max.

Control of focus: manual

Viewing angle: 100°

Lens type: auto aperture (DC)

Compression: H. 264 / H. 264H / H. 264B / MJPEG

Resolution: 3M (2304×1296) / 1080P (1920×1080) / 720P (1280×720) / VGA (640×480) / QVGA (320×240)

Refresh rate:

Main stream: 3M (from 1 fps to 20 fps) / 1080p (from 1 fps to 25 / 30 fps)

Substream: VGA / QVGA (from 1 fps to 25/30 fps)

Bit-rate: H.264 - from 32 kbps to 8192 kbps

Ethernet: RJ-45 (10/100 Base-T)

WiFi range: up to 50 meters (open space)

Protocol: IPv4/IPv6, HTTP, HTTPS, TCP/IP, UDP, UPnP, ICMP, IGMP, RTSP, RTP, SMTP, NTP, DHCP, DNS,

PPPOE, DDNS, FTP, IP Filter, QoS

Number of users: up to 20

Supported mobile operating systems: iOS, Android, Windows Phone

Memory slot: micro SD up to 128 GB

Operating temperature: -30°C to 50°C

Humidity: up to 95%

Level of protection: IP67

Size: F70 × 165 mm
Weight: 0.49 kg