Firma: PC COOL DOO
Adresa: Višegradska 26A
Telefon: 0653526116
Fax:
PIB: 104045201
E-mail: info@pccool.rs

Dahua Mrezni kabal Cat5 DH-PFM920I-5EUN UTP BAKARNI 305m

Šifra: 18374
Kategorija prozivoda: Mrežna oprema
Proizvođač: DAHUA

Cena: 19.280,00



-305 m (1000 ft)/karton UTP CAT5e, napajanje preko Etherneta, kompatibilan sa jednim kablom
-Bakarni provodnik oxygen-free visoke cistoce
-Prilagodeni PVC spoljni omotac; CE CPR Eca sertifikovana klasa otpornosti na vatru

Material: Oxygen free copper (99.97% purity)
Diameter: 0.45 mm ± 0.01 mm
Insulation
Material: HDPE
Min. Average Thickness: 0.18 mm
Diameter: 0.81mm±0.1mm
Color (4 Pairs): Blue, white/blue; orange, white/orange; green, white/green; brown, white/brown

Rip Cord
Material: Polyester
Specification: 500D

Sheath
Material: PVC
Min. Average Thickness: 0.5 mm
Diameter: 4.7 mm ± 0.3 mm
Color: White

Electrical
Max. DC Resistance of a Single Conductor: 12O/100 m
Min. Insulation Resistance: 5000MO·km
Max. DC Resistance Unbalance: 2% (pair intra), 4% (pairs inter)
Dielectric Strength: No breakdown with 1KV DC for 1 min

Transmission
Characteristic Impedance: 100 ± 15O
Near End Cross Talk: =35.30 dB/100 m@100 MHz
Max. Attenuation: 24.2 dB/100 m@100 MHz
Return Loss: =20.1 dB/100 m@100 MHz

Mechanical
Tensile Strength:
Sheath=13.5 MPa, insulation=16 MPa
Elongation at Break: Sheath=150%, insulation=300%
Installation Bending Radius: >8 times of outer cable diameter
Conductor Elongation at Break: =10%

Environmental
Shrinkage of Insulation: =5%
Color Migration Resistance of Insulation: No migration
Sheath Tensile Strength and Elongation at Break after Aging: =12.5 MPa, =100%
Low Temperature Bending Test: No cracking after the test
Heat Shock Test: No cracking after the test
Operating Temperature: –20°C to +60°C (–4°F to 140°F)
Installation Temperature: 0°C to +50°C (32°F to 122°F)

Storage Temperature and Humidity: –10°C to +40°C (14°F to 104°F), <60% (RH)

Security
Vertical Fire Propagation Test: Comply with IEC 60332-1-2

Packaging
Cable Length: 305.0 m (1000.66 ft) ± 1.5 m (4.92 ft)
Inner Carton Dimensions: 364.0 mm × 364.0 mm × 216.0 mm
(14.33" × 14.33" × 8.50") (L × W × H)

Packaging Method: 305.0 m (1000.66 ft) a carton, one master carton with 2 inner cartons
Net Weight: =7.0 kg (15.43 lb)
Gross Weight: =8.0 kg (17.64 lb)

Cene su informativnog karaktera. Prodavac ne odgovara za tačnost cena iskazanih na sajtu, zadržava pravo izmena cena. Ponudu za ostale artikle, informacije o stanju lagera i aktuelnim cenama možete dobiti na upit. Plaćanje se isključivo vrši virmanski - bezgotovinski.