

logo not found or type unknown

Firma: PC COOL DOO  
Adresa: Višegradaska 26A  
Telefon: 018526116  
Fax: 0653526116  
PIB: 104045201  
E-mail: info@pccool.rs

## Napajanje 850W Seasonic B12 BC 80+ Bronze Series

Šifra: 18503  
Kategorija proizvoda: Napajanja  
Proizvođač: Seasonic



Cena: **13.725,00**

| Technical Specifications    |                          |        |                                                             |       |       |        |
|-----------------------------|--------------------------|--------|-------------------------------------------------------------|-------|-------|--------|
| 80PLUS®                     |                          |        | Bronze                                                      |       |       |        |
| Cybenetics Efficiency Level |                          |        | TBA                                                         |       |       |        |
| Cybenetics Noise Level      |                          |        | TBA                                                         |       |       |        |
| Form Factor                 |                          |        | Intel ATX 12 V                                              |       |       |        |
| Dimensions                  |                          |        | 140 mm (L) x 150 mm (W) x 86 mm (H)                         |       |       |        |
| Fan Information             | Fan Size                 |        | 120 mm                                                      |       |       |        |
|                             | Fan Control              |        | Smart and Silent Fan Control                                |       |       |        |
|                             | Fan Bearing              |        | Sleeve Bearing                                              |       |       |        |
|                             | Life Expectancy          |        | 25,000 hours at 40 °C, 15 % - 65 % RH                       |       |       |        |
| Cable Information           | Modularity               |        | Fixed cables                                                |       |       |        |
|                             | Cable type               |        | Flat black cables                                           |       |       |        |
| Electrical Features         | Operating Temperature    |        | 0 - 50 °C (derating from 100 % to 80 % from 40 °C to 50 °C) |       |       |        |
|                             | MTBF @ 25 °C, excl. fan  |        | 100,000 hours                                               |       |       |        |
|                             | AC Input                 |        | Full Range                                                  |       |       |        |
|                             | Protection               |        | OPP, OVP, OCP, SCP                                          |       |       |        |
| Safety and Environmental    | Safety and EMC           |        | cTUVus, TUV, CB, CCC, BSMI, CE, FCC                         |       |       |        |
|                             | Environmental Compliance |        | Energy Star, RoHS, WEEE, ErP Lot 6, REACH                   |       |       |        |
| Warranty                    |                          |        | 5 Years                                                     |       |       |        |
| Power Output                |                          |        |                                                             |       |       |        |
| AC Input                    | Voltage: 100 V - 240 V   |        |                                                             |       |       |        |
|                             | Current: 10 A Max.       |        |                                                             |       |       |        |
|                             | Frequency: 50 Hz - 60 Hz |        |                                                             |       |       |        |
| DC Output                   | Rail                     | +3.3 V | +5 V                                                        | +12 V | -12 V | +5 VSB |
|                             | Maximum Power            | 15 A   | 15 A                                                        | 70 A  | 0.3 A | 2.5 A  |
|                             |                          | 100 W  |                                                             | 840 W | 3.6 W | 12.5 W |
|                             | Total continuous power   |        | 850 W                                                       |       |       |        |

## Cables

### B12-BC-850

| Cable type      | Connector(s) per cable | Total length (mm) | Number(s) of cable(s) included |
|-----------------|------------------------|-------------------|--------------------------------|
| MB (24/20 pins) | 1                      | 550               | 1                              |
| CPL (8 pins)    | 1                      | 700               | 0                              |
| CPL (4/8 pins)  | 1                      | 600               | 2                              |
| PCI (8/6 pins)  | 2                      | 700               | 0                              |
| PCI (8/6 pins)  | 1                      | 550               | 3                              |
| SATA 4x 90      | 4                      | 810               | 0                              |
| SATA 4x 180     | 4                      | 860               | 0                              |

|                                                                                 | Cable type                                                       | Connector(s) per cable | Total length (mm) | Number(s) of cable(s) included |
|---------------------------------------------------------------------------------|------------------------------------------------------------------|------------------------|-------------------|--------------------------------|
|   | SATA to SATA 4x90<br>Image not found or type unknown             | 4                      | 760               | 0                              |
|  | ATA to SATA 3x<br>Image not found or type unknown                | 3                      | 690               | 2                              |
|  | SATA to SATA 2x90<br>Image not found or type unknown             | 2                      | 700               | 0                              |
|  | SATA to SATA 2x180<br>Image not found or type unknown            | 2                      | 600               | 0                              |
|  | SATA to SATA 2x180<br>Image not found or type unknown            | 2                      | 470               | 0                              |
|  | SATA to SATA 2x180<br>Image not found or type unknown            | 2                      | 450               | 0                              |
|  | Molex to SATA 3x<br>Image not found or type unknown              | 3                      | 690               | 1                              |
|  | Molex to SATA 2x<br>Image not found or type unknown              | 2                      | 470               | 0                              |
|  | Molex to SATA 3-3-300 Adapter<br>Image not found or type unknown | 2                      | 300               | 0                              |
|  | Molex to FDD-101 Adapter<br>Image not found or type unknown      | 1                      | 101               | 0                              |