

LAN Switch TP-LINK TL-SG1024DE 101001000 24p

Šifra: 18539
 Kategorija proizvoda: Mrežna oprema
 Proizvođač: TP-Link



Cena: 13.090,00

HARDWARE FEATURES	
Standards and Protocols	IEEE 802.3i IEEE 802.3u IEEE 802.3ab IEEE 802.3x IEEE 802.1q IEEE 802.1p
Interface	24 10/100/1000Mbps RJ45 Ports AUTO Negotiation/AUTO MDI/MDIX
Network Media	10BASE-T: UTP category 3, 4, 5 cable (maximum 100m) EIA/TIA-568 100Ω STP (maximum 100m) 100BASE-TX: UTP category 5, 5e cable (maximum 100m) EIA/TIA-568 100Ω STP (maximum 100m) 1000BASE-T: UTP category 5, 5e, 6 or above cable (maximum 100m) EIA/TIA-568 100Ω STP (maximum 100m)
Fan Quantity	Fanless
Physical Security Lock	No
Power Supply	100-240VAC, 50/60Hz
Dimensions (W x D x H)	11.6 x 7.1 x 1.7 in. (294 x 180 x 44 mm)
Mounting	Rack Mountable
Max Power Consumption	14.19W (220V/50Hz)
Max Heat Dissipation	48.39 BTU/h
PERFORMANCE	
Switching Capacity	48Gbps
Packet Forwarding Rate	35.7Mpps
MAC Address Table	8K
Packet Buffer Memory	4.1Mbit
Jumbo Frame	10KB
SOFTWARE FEATURES	
Quality of Service	Support Port-based/802.1p/DSCP priority Support 4 priority queues Rate Limit Storm Control
L2 Features	IGMP Snooping V1/V2/V3 Static Link Aggregation Port Mirroring Cable Diagnostics Loop Prevention
VLAN	Supports up to 32 VLANs simultaneously (out of 4K VLAN IDs) MTU/Port/Tag VLAN

SOFTWARE FEATURES

Transmission Method	Store-And-Forward
----------------------------	-------------------

OTHERS

Certification	FCC, CE, RoHS
----------------------	---------------

Package Contents	TL-SG1024DE Power Cord Installation Guide Resource CD Rackmount Kit Rubber Feet
-------------------------	--

System Requirements	Microsoft® Windows® for Easy Smart Utility
----------------------------	--

Environment	Operating Temperature: 0?~40? (32?~104?) Storage Temperature: -40?~70? (-40?~158?) Operating Humidity: 10%~90% non-condensing Storage Humidity: 5%~90% non-condensing
--------------------	--