

TP-Link Archer T2U AC600 wireless 600Mbps dual band USB

Šifra: 18630
Kategorija proizvoda: Mrežna oprema
Proizvođač: TP-Link

Cena: 1.510,00



HARDWARE FEATURES	
Interface	USB 2.0
LED	Status
Dimensions (W x D x H)	1.6×0.7×0.3 in. (41×19.5×8.7mm)
Antenna Type	Omni Directional
WIRELESS FEATURES	
Wireless Standards	IEEE 802.11ac, IEEE 802.11a, IEEE 802.11n, IEEE 802.11g, IEEE 802.11b
Frequency	5GHz 2.4GHz
Signal Rate	5GHz 11ac: Up to 433Mbps(dynamic) 11n: Up to 150Mbps(dynamic) 11a: Up to 54Mbps(dynamic) 2.4GHz 11n: Up to 150Mbps(dynamic) 11g: Up to 54Mbps(dynamic) 11b: Up to 11Mbps(dynamic)
Reception Sensitivity	5GHz: 11a 6Mbps: -94dBm 11a 54Mbps: -78dBm 11n HT20 MCS0: -94dBm 11n HT20 MCS7: -77dBm 11n HT40 MCS0: -92dBm 11n HT40 MCS7: -74dBm 11ac VHT80 MCS0: -89dBm 11ac VHT80 MCS9: -64dBm 2.4GHz: 11b 1Mbps: -99dBm 11b 11Mbps: -91dBm 11g 6Mbps: -94dBm 11g 54Mbps: -77dBm 11n HT20 MCS0: -95dBm 11n HT20 MCS7: -76dBm 11n HT40 MCS0: -92dBm 11n HT40 MCS7: -73dBm
Transmit Power	<20dBm (EIRP)
Wireless Modes	Ad-Hoc / Infrastructure mode
Wireless Security	Support 64/128 bit WEP, WPA-PSK/WPA2-PSK, 802.1x
Modulation Technology	DBPSK, DQPSK, CCK, OFDM, 16-QAM, 64-QAM, 256-QAM
OTHERS	
Certification	FCC, RoHS

OTHERS	
Package Contents	Wireless Adapter Archer T2U Resource CD Quick Installation Guide
System Requirements	Windows & MacOS
Environment	Operating Temperature: 0?~40? (32?~104?) Storage Temperature: -40?~70? (-40?~158?) Operating Humidity: 10%~90% non-condensing Storage Humidity: 5%~90% non-condensing