

TP-LINK RE200 Wi-Fi Range Extender AC750

Šifra: 19463
Kategorija proizvoda: Mrežna oprema
Proizvođač: TP-Link

Cena: 3.450,00



HARDWARE FEATURES	
Plug Type	EU, UK, US, AU
Standards and Protocols	IEEE802.11ac, IEEE 802.11n, IEEE 802.11g, IEEE 802.11b
Interface	1 x 10/100M Ethernet Port (RJ45)
Button	RE (Range Extender) Button, Reset Button
Power Consumption	About 6.5W
Dimensions (W x D x H)	4.3x 2.6 x 3.0in. (110.0 x 65.8 x 75.2mm)
Antenna	3 x internal
WIRELESS FEATURES	
Frequency	2.4GHz & 5GHz
Signal Rate	5GHz: Up to 433Mbps 2.4GHz: Up to 300Mbps
Reception Sensitivity	2.4G: 270M: -70dBm@10% PER 130M: -70dBm@10% PER 108M: -73dBm@10% PER 54M: -75dBm@10% PER 11M: -86dBm@8% PER 6M: -92dBm@10% PER 1M: -94dBm@8% PER 5G: 390M: -60dBm@10% PER 29.3M: -83dBm@10% PER 180M: -64dBm@10% PER 13.5M: -87dBm@10% PER 78M: -68dBm@10% PER 6.5M: -90dBm@10% PER 54M: -75dBm@10% PER 6M: -90dBm@10% PER
Transmit Power	< 20 dBm (EIRP)
Wireless Modes	Range Extender/Access Point
Wireless Functions	WMM (Wi-Fi Multimedia) Wireless Statistic Domain Login Function
Wireless Security	64/128/152-bit WEP WPA-PSK / WPA2-PSK
OTHERS	
Certification	CE, FCC, RoHS
Package Contents	AC750 Wi-Fi Range Extender RE200 Quick Installation Guide

OTHERS

System Requirements	Microsoft® Windows® 98SE, NT, 2000, XP, Vista or Windows 7, 8, 10, Mac® OS, NetWare®, UNIX® or Linux.
Environment	Operating Temperature: 0°C~40°C (32°F~104°F) Storage Temperature: -40°C~70°C (-40°F~158°F) Operating Humidity: 10%~90% non-condensing Storage Humidity: 5%~90% non-condensing