Firma: PC COOL DOO
Adresa: Višegradska 26A
Telefon: 0653526116
Fax:
PIB: 104045201
E-mail: info@pccool.rs

IP-COM G1016D LAN 16-Port 10/100/1000M Base-T/TX Ethernet ports (MDI/MDIX) Desk or rack(alt=TEG1016D



Šifra: 19494
Kategorija prozivoda: Mrežna oprema
Proizvođač: IP-COM

Cena: 6.570,00

IP-COM G1016D is a 16-port gigabit unmanaged desktop/rack switch designed for video surveillance in offices, work groups, and SMEs for easy, economical and high-speed internet purposes. Its full duplex transmission rate can reach up to 2000 Mbps, ensuring the timely transfer of large files as well as smooth streaming videos. The professional integrated lightening protection circuit, the built-in power supply module, and all the 16 ports could withstand 6 kV lightning surge, ensuring the switch to run stably. G1016D is your ideal choice for extension, or upgrade to high-speed and stable gigabit wired network.

Compliant with IEEE802.3, IEEE802.3u, IEEE802.3X, IEEE802.3ab standards
16*10/100/1000 Mbps auto-negotiation RJ45 ports
Auto MDI/MDIX
8K MAC address ,MAC auto Learning & Auto Aging
IEEE 802.3x full duplex flow control, and backpressure half duplex flow control
32 Gbps switching fabric for non-blocking line-speed forwarding
LED indicators for indicating working status and troubleshooting
Built-in power supply system with 6 kV common mode and 4 kV differtiatial mode lightning protection
16 ports all with 6 kV common mode lightning protection
IP camera connection
Plug and play

Standard IEEE 802.3?IEEE 802.3u?IEEE 802.3x?IEEE 802.3ab
Forwarding Speed 10Mbps : 14880pps
100Mbps : 148800pps
1000Mbps : 1488000pps
Transmission Media 10BASE-T: UTP category 3, 4, 5 cable
100BASE-TX/1000BASE-T: UTP category 5, 5e or above cable
Port 16*10/100/1000Mbps auto-negotiation RJ45 ports (Auto MDI/MDIX)
LED Indication 16*Link/Act indicator,1*power indicator
Dimensions 294mm×178mm×44mm
Switch Feature Store-and-Forward
MAC auto Learning & Auto Aging
8K MAC
32Gbps Backpanel bandwidth
Lighting Proof lightning protection 6KV for power supply,6KV for all ports
Power Input 100~240V AC,50/60Hz
Operating Environment Temperature:0?~45?

Cene su informativnog karaktera. Prodavac ne odgovara za tačnost cena iskazanih na sajtu, zadržava pravo izmena cena. Ponudu za ostale artikle, informacije o stanju lagera i aktuelnim cenama možete dobiti na upit. Plaćanje se isključivo vrši virmanski - bezgotovinski.