Firma: PC COOL DOO
Adresa: Višegradska 26A
Telefon: 0653526116
Fax:
PIB: 104045201
E-mail: info@pccool.rs

LAN Router TP-Link Archer AX10 AX1500WiFi64GLAN

Šifra: 21369
Kategorija prozivoda: Mrežna oprema
Proizvođač: TP-Link

Cena: 7.010,00



WIRELESS	
Standards	**Wi-Fi 6** IEEE 802.11ax/ac/n/a 5 GHz IEEE 802.11n/b/g 2.4 GHz
WiFi Speeds	**AX1500** 5 GHz: 1201 Mbps (802.11ax) 2.4 GHz: 300 Mbps (802.11n)
WiFi Range	**2-3 Bedroom Houses** 4× Fixed High-Performance Antennas Multiple antennas form a signal-boosting array to cover more directions and large areas Beamforming Concentrates wireless signal strength towards clients to expand WiFi range
WiFi Capacity	**High** Dual-Band Allocate devices to different bands for optimal performance OFDMA Simultaneously communicates with multiple Wi-Fi 6 clients Airtime Fairness Improves network efficiency by limiting excessive occupation 4 Streams Connect your devices to more bandwidth
Working Modes	Router Mode Access Point Mode

HARDWARE	
Processor	1.5 GHz Triple-Core CPU
Ethernet Ports	1× Gigabit WAN Port 4× Gigabit LAN Ports
Buttons	WPS/Wi-Fi Button Power On/Off Button Reset Button
Power	12 V ? 1 A

SECURITY	
WiFi Encryption	WPA WPA2

SECURITY	
	WPA3 WPA/WPA2-Enterprise (802.1x)
Network Security	SPI Firewall Access Control IP & MAC Binding Application Layer Gateway
Guest Network	1× 5 GHz Guest Network 1× 2.4 GHz Guest Network
VPN Server	OpenVPN PPTP

SOFTWARE	
Protocols	IPv4 IPv6
OneMesh™	OneMesh™ Supported Without replacing your existing devices or buying a whole new WiFi ecosystem, OneMesh™ helps you create a more flexible network that covers your entire home with TP-Link OneMesh™ products. Learn More> All OneMesh Products>
Parental Controls	URL Filtering Time Controls
WAN Types	Dynamic IP Static IP PPPoE PPTP L2TP
Quality of Service	QoS by Device
Cloud Service	Auto Firmware Upgrade OTA Firmware Upgrade TP-Link ID DDNS
NAT Forwarding	Port Forwarding Port Triggering DMZ UPnP
IPTV	IGMP Proxy IGMP Snooping Bridge Tag VLAN
DHCP	Address Reservation DHCP Client List Server
DDNS	TP-Link NO-IP DynDNS
Management	Tether App Webpage Check Web Emulator>

PHYSICAL	
Dimensions (W×D×H)	10.2 × 5.3 ×1.5 in (260.2 × 135.0 × 38.6 mm)
Package Contents	Wi-Fi Router Archer AX10 Power Adapter RJ45 Ethernet Cable Quick Installation Guide

OTHER	
System Requirements	Internet Explorer 11+, Firefox 12.0+, Chrome 20.0+, Safari 4.0+, or other JavaScript-enabled browser

OTHER	
	Cable or DSL Modem (if needed) Subscription with an internet service provider (for internet access)
Certifications	FCC
Environment	Operating Temperature: 0?~40? (32? ~104?) Storage Temperature: -40?~70? (-40? ~158?) Operating Humidity: 10%~90% non-condensing Storage Humidity: 5%~90% non-condensing

TEST DATA	
WiFi Transmission Power	FCC: <30dBm(2.4 GHz & 5.15 GHz~5.825 GHz)
WiFi Reception Sensitivity	5 GHz: 11a 6Mbps:-97dBm 11a 54Mbps:-79dBm 11ac VHT20_MCS0:-96dBm 11ac VHT20_MCS11:-66dBm 11ac VHT40_MCS0:-94dBm 11ac VHT40_MCS11:-63dBm 11ac VHT80_MCS0:-91dBm 11ac VHT80_MCS11:-60dBm 11ax HE20_MCS0:-95dBm 11ax HE20_MCS11:-63dBm 11ax HE40_MCS0:-92dBm 11ax HE40_MCS11:-60dBm 11ax HE80_MCS0:-89dBm 11ax HE80_MCS11:-58dBm 2.4 GHz: 11g 6Mbps:-91dBm 11a 54Mbps:-74dBm 11n HT20_MCS0:-90dBm 11n HT20_MCS7:-73dBm 11n HT40_MCS0:-88dBm

Cene su informativnog karaktera. Prodavac ne odgovara za tačnost cena iskazanih na sajtu, zadržava pravo izmena cena. Ponudu za ostale artikle, informacije o stanju lagera i aktuelnim cenama možete dobiti na upit. Plaćanje se isključivo vrši virmanski - bezgotovinski.