

MB AM4 GIGABYTE B550 AORUS ELITE AX rev. 2.0

Šifra: 22244
Kategorija proizvoda: Matične ploče
Proizvođač: GIGABYTE

Cena: 19.070,00



CPU AMD Socket AM4, support for: AMD Ryzen™ 5000 Series/ Ryzen™ 5000 G-Series/ Ryzen™ 4000 G-Series and Ryzen™ 3000 Series Processors (Please refer "CPU Support List" for more information.)	Chipset AMD B550	Memory 4 x DDR4 support (32 G capac mem
	Onboard Graphics Integrated Graphics Processor: 1 x DisplayPort, supporting a maximum resolution of 5120x2880@60 Hz * Support for DisplayPort 1.4 version, HDCP 2.3, and HDR. 1 x HDMI port, supporting a maximum resolution of 4096x2160@60 Hz * Support for HDMI 2.1 version, HDCP 2.3, and HDR.	Audio
	Maximum shared memory of 16 GB	(Please informa

Realtek® ALC1200 codec	High Definition Audio 2/4/5.1/7.1-channel Support for S/PDIF Out	LAN Realtek® 2.5GbE LAN chip (2.5 Gbit/1 Gbit/100 Mbit)	Wireless Intel® WiFi 6 wave 2 support Dual- band
		Expansion Slots 1 x PCI Express x16 slot (PCIEX16), integrated in the CPU: AMD Ryzen™ 5000 Series and Ryzen™ 3000 Series Processors support PCIe 4.0 x16 mode	1 x M.2 (M2A) in the Socket 2242 SSDs - AMD Series Series suppo 4.0 x - AMD 5000 Ryzen Proce and P
		AMD Ryzen™ Ryzen™ 5000 G-Series and Ryzen™ 4000 G-Series Processors support PCIe 3.0 x16 mode * For optimum performance, if only one PCI Express graphics card is to be installed, be sure to install it in the PCIEX16 slot.	
		1 x PCI Express x16 slot (PCIEX2), integrated in the Chipset: Supporting PCIe 3.0 x2 mode	
		1 x PCI Express x16 slot (PCIEX1_2), integrated in the Chipset: Supporting PCIe 3.0 x1 mode	
		1 x PCI Express x1 slot (PCIEX1_1), integrated in the Chipset: Supporting PCIe 3.0 x1 mode	
		USB CPU: 2 x USB 3.2 Gen 2 Type- A ports (red) on the back panel	Internal 1 x 2 powe
		2 x USB 3.2 Gen 1 ports on the back panel	
		Chipset: 1 x USB Type-C™ port with USB 3.2 Gen 1 support, available through the internal USB header	1 x USB 3.2 Gen 1 port on the back panel
			2 x USB 3.2 Gen 1 ports available through the internal USB header 2 x USB 2.0/1.1 ports on the back panel
		Chipset+USB 2.0 Hub: 4 x USB 2.0/1.1 ports available through the internal USB headers	

(2x6 pin, for the GC-TPM2.0_S module only) *All fan headers are subject to support AIO_Pump, Pump and high performance fan with the capability of delivering up to 2A/12V @ 24W.	1 x Clear CMOS jumper	Back Panel Connectors	1 x DisplayPort	1 x HDMI port 2 x SMA antenna connectors (2T2R)	I/O Controller iTE®
				2 x USB 3.2 Gen 2 Type-A ports (red) 3 x USB 3.2 Gen 1 ports 2 x USB 2.0/1.1 ports 1 x Q-Flash Plus button 1 x RJ-45 port 1 x optical S/PDIF Out connector 5 x audio jacks	
		H/W Monitoring	Voltage detection	Temperature detection Fan speed detection Water cooling flow rate detection Overheating warning Fan fail warning Fan speed control * Whether the fan speed control function is supported will depend on the fan you install.	BIOS 1 x 2
		Unique Features	Support for APP Center * Available applications in APP Center may vary by motherboard model. Supported functions of each application may also vary depending on motherboard specifications. @BIOS EasyTune Fast Boot Game Boost ON/OFF Charge RGB Fusion Smart Backup System Information Viewer	Support for Q-Flash Plus Support for Q-Flash Support for Xpress Install	Bundle Norton Security
		Operating System	Support for Windows 11 64-bit	Support for Windows 10 64-bit	Form Factor ATX Form Factor 30.5cm