Firma: PC COOL DOO
Adresa: Višegradska 26A
Telefon: 0653526116
Fax:
PIB: 104045201
E-mail: info@pccool.rs

# MB s1200 ASUS PRIME H410M-ACSM

Šifra: 22246
Kategorija prozivoda: Matične ploče
Proizvođač: ASUS

Cena: 9.970,00




## CPU
Intel®
Socket

1200 for 10th Gen Intel® Core™, Pentium® Gold and Celeron® Processors *
Supports Intel® 14 nm CPU
Supports Intel® Turbo Boost Technology 2.0 and Intel® Turbo Boost Max Technology 3.0**
* Refer to www.asus.com for CPU support list
**Intel® Turbo Boost Max Technology 3.0 support depends on the CPU types.

## Chipset
Intel® H410

## Memory
2 x DIMM, Max. 64GB, DDR4 2933/2800/2666/2400/2133 MHz Non-ECC, Un-buffered Memory *
Dual Channel Memory Architecture
Supports Intel® Extreme Memory Profile (XMP)
OptiMem
* 10th Gen Intel® Core™ i9/i7 CPUs support 2933/2800/2666/2400/2133 natively, Refer to www.asus.com for the Memory QVL (Qualified Vendors Lists).

## Graphic
Integrated Graphics Processor *
1 x D-Sub
1 x DVI-D
1 x HDMI 1.4b
*Graphics specifications may vary between CPU types.

## Expansion Slots
**Intel® 10th Gen Processors**
1 x PCIe 3.0 x16 (x16 mode)
**Intel® H410 Chipset**
2 x PCIe 3.0 x1

## Storage
**Total supports 1 x M.2 slots and 4 x SATA 6Gb/s ports**
**Intel® H410 Chipset :**
1 x M.2 Socket 3, with M Key, type 2242/2260/2280 storage devices support (SATA & PCIE 3.0 X2 mode)*[1]
4 x SATA 6Gb/s port(s)

## LAN
Realtek® RTL8111H

## Audio
Realtek ALC887 7.1-Channel High Definition Audio CODEC *[2]
- Supports : Jack-detection, Multi-streaming, Front Panel Jack-retasking, up to 24-Bit/192kHz playback
**Audio Feature :**
- LED-illuminated design
- Audio Shielding
- Dedicated audio PCB layers
- Premium Japanese audio capacitors

## USB Ports

**Rear USB Port** ( Total 4 )
2 x USB 3.2 Gen 1 port(s)(2 x Type-A)
2 x USB 2.0 port(s)(2 x Type-A)
**Front USB Port** ( Total 6 )
2 x USB 3.2 Gen 1 port(s)
4 x USB 2.0 port(s)

# Software Features

ASUS Exclusive Software
Armoury Crate
AI Suite 3
- Performance And Power Saving Utility
TurboV EVO
EPU
Digi+ VRM
Fan Xpert 2+
- EZ update
ASUS CPU-Z
AI Charger
DAEMON Tools
Norton Anti-virus software (Free Trial for 60 days)
WinRAR
UEFI BIOS
ASUS EZ DIY
- ASUS CrashFree BIOS 3
- ASUS EZ Flash 3
- ASUS UEFI BIOS EZ Mode

# ASUS Special Features

ASUS 5X PROTECTION III
- ASUS DIGI+ VRM
- ASUS LANGuard
- ASUS Overvoltage Protection
- ASUS SafeSlot Core
- ASUS Stainless-Steel Back I/O
ASUS Q-Design
- ASUS Q-DIMM
- ASUS Q-Slot
ASUS Thermal Solution
- Aluminum heatsink design

# Back I/O Ports

1 x PS/2 keyboard (purple)
1 x PS/2 mouse (green)
1 x DVI-D
1 x D-Sub
1 x HDMI
1 x LAN (RJ45) port(s)
2 x USB 3.2 Gen 1 Type-A
2 x USB 2.0
3 x Audio jack(s)

# Internal I/O Ports

1 x CPU Fan connector(s)
2 x Chassis Fan connector(s)
1 x USB 3.2 Gen 1(up to 5Gbps) connector(s) support(s) additional 2 USB 3.2 Gen 1 port(s)
2 x USB 2.0 connector(s) support(s) additional 4 USB 2.0 port(s)
1 x M.2 Socket 3 with M Key, type 2242/2260/2280 storage devices support (SATA & PCIE 3.0 X2 mode)
1 x SPI TPM header
1 x COM port(s) connector(s)
4 x SATA 6Gb/s connector(s)
1 x S/PDIF out header(s)
1 x 24-pin EATX Power connector(s)
1 x 8-pin EATX 12V Power connectors
1 x Front panel audio connector(s) (AAFP)
1 x Clear CMOS jumper(s)
1 x System panel connector
1 x Speaker connector

# Accessories

1 x ACC Express Activation Key Card
I/O Shield
2 x SATA 6Gb/s cable(s)
1 x M.2 Anchor
1 x Supporting DVD
User manual

## BIOS
128 Mb Flash ROM, UEFI AMI BIOS
## Manageability
WOL by PME, PXE
## Operating System
Windows® 10 64-bit

Cene su informativnog karaktera. Prodavac ne odgovara za tačnost cena iskazanih na sajtu, zadržava pravo izmena cena. Ponudu za ostale artikle, informacije o stanju lagera i aktuelnim cenama možete dobiti na upit. Plaćanje se isključivo vrši virmanski - bezgotovinski.