

MB s1200 ASUS PRIME H410M-ACSM

Šifra: 22246

Kategorija proizvoda: Matične ploče

Proizvođač: ASUS

Cena: **9.970,00**



CPU

Intel® Socket 1200 for 10th Gen Intel® Core™, Pentium® Gold and Celeron® Processors *

Supports Intel® 14 nm CPU

Supports Intel® Turbo Boost Technology 2.0 and Intel® Turbo Boost Max Technology 3.0**

* Refer to www.asus.com for CPU support list

**Intel® Turbo Boost Max Technology 3.0 support depends on the CPU types.

Chipset

Intel® H410

Memory

2 x DIMM, Max. 64GB, DDR4 2933/2800/2666/2400/2133 MHz Non-ECC, Un-buffered Memory *

Dual Channel Memory Architecture

Supports Intel® Extreme Memory Profile (XMP)

OptiMem

* 10th Gen Intel® Core™ i9/i7 CPUs support 2933/2800/2666/2400/2133 natively, Refer to www.asus.com for the Memory QVL (Qualified Vendors Lists).

Graphic

Integrated Graphics Processor *

1 x D-Sub

1 x DVI-D

1 x HDMI 1.4b

*Graphics specifications may vary between CPU types.

Expansion Slots

Intel® 10th Gen Processors

1 x PCIe 3.0 x16 (x16 mode)

Intel® H410 Chipset

2 x PCIe 3.0 x1

Storage

Total supports 1 x M.2 slots and 4 x SATA 6Gb/s ports

Intel® H410 Chipset :

1 x M.2 Socket 3, with M Key, type 2242/2260/2280 storage devices support (SATA & PCIE 3.0 X2 mode)*1

4 x SATA 6Gb/s port(s)

LAN

Realtek® RTL8111H

Audio

Realtek ALC887 7.1-Channel High Definition Audio CODEC *2

- Supports : Jack-detection, Multi-streaming, Front Panel Jack-retasking, up to 24-Bit/192kHz playback

Audio Feature :

- LED-illuminated design

- Audio Shielding
- Dedicated audio PCB layers
- Premium Japanese audio capacitors

USB Ports

Rear USB Port (Total 4)

2 x USB 3.2 Gen 1 port(s)(2 x Type-A)

2 x USB 2.0 port(s)(2 x Type-A)

Front USB Port (Total 6)

2 x USB 3.2 Gen 1 port(s)

4 x USB 2.0 port(s)

Software Features

ASUS Exclusive Software

Armoury Crate

AI Suite 3

- Performance And Power Saving Utility

TurboV EVO

EPU

Digi+ VRM

Fan Xpert 2+

- EZ update

ASUS CPU-Z

AI Charger

DAEMON Tools

Norton Anti-virus software (Free Trial for 60 days)

WinRAR

UEFI BIOS

ASUS EZ DIY

- ASUS CrashFree BIOS 3

- ASUS EZ Flash 3

- ASUS UEFI BIOS EZ Mode

ASUS Special Features

ASUS 5X PROTECTION III

- ASUS DIGI+ VRM

- ASUS LANGuard

- ASUS Overvoltage Protection

- ASUS SafeSlot Core

- ASUS Stainless-Steel Back I/O

ASUS Q-Design

- ASUS Q-DIMM

- ASUS Q-Slot

ASUS Thermal Solution

- Aluminum heatsink design

Back I/O Ports

1 x PS/2 keyboard (purple)

1 x PS/2 mouse (green)

1 x DVI-D

1 x D-Sub

1 x HDMI

1 x LAN (RJ45) port(s)

2 x USB 3.2 Gen 1 Type-A

2 x USB 2.0

3 x Audio jack(s)

Internal I/O Ports

1 x CPU Fan connector(s)

2 x Chassis Fan connector(s)

1 x USB 3.2 Gen 1(up to 5Gbps) connector(s) support(s) additional 2 USB 3.2 Gen 1 port(s)

2 x USB 2.0 connector(s) support(s) additional 4 USB 2.0 port(s)

1 x M.2 Socket 3 with M Key, type 2242/2260/2280 storage devices support (SATA & PCIE 3.0 X2 mode)

1 x SPI TPM header

1 x COM port(s) connector(s)
4 x SATA 6Gb/s connector(s)
1 x S/PDIF out header(s)
1 x 24-pin EATX Power connector(s)
1 x 8-pin EATX 12V Power connectors
1 x Front panel audio connector(s) (AAFP)
1 x Clear CMOS jumper(s)
1 x System panel connector
1 x Speaker connector

Accessories

1 x ACC Express Activation Key Card
I/O Shield
2 x SATA 6Gb/s cable(s)
1 x M.2 Anchor
1 x Supporting DVD
User manual

BIOS

128 Mb Flash ROM, UEFI AMI BIOS

Manageability

WOL by PME, PXE

Operating System

Windows® 10 64-bit

Form Factor

mATX Form Factor

8.9 inch x 8.0 inch (22.6 cm x 20.3 cm)