Firma: PC COOL DOO
Adresa: Višegradska 26A
Telefon: 0653526116
Fax:
PIB: 104045201
E-mail: info@pccool.rs

MB s1700 Gigabyte B660 GAMING X AX

Šifra: 22252
Kategorija prozivoda: Matične ploče
Proizvođač: GIGABYTE

Cena: 25.080,00



CPU

LGA1700 socket: Support for 12th Generation Intel® Core™, Pentium® Gold and Celeron® Processors*	L3 cache varies with CPU

* Please refer to "CPU Support List" for more information.

Memory

Support for DDR4 4400(O.C.)/ 4300(O.C.)/4266(O.C.) / 4133(O.C.) / 4000(O.C.) / 3866(O.C.) / 3800(O.C.) / 3733(O.C.) / 3666(O.C.) / 3600(O.C.) / 3466(O.C.) / 3400(O.C.) / 3333(O.C.) / 3300(O.C.) /3200/3000/2933/2666/2400/2133 MHz memory modules	4 x DDR DIMM sockets supporting up to 128 GB (32 GB single DIMM capacity) of system memory
Dual channel memory architecture	Support for ECC Un-buffered DIMM 1Rx8/2Rx8 memory modules (operate in non-ECC mode)
Support for non-ECC Un-buffered DIMM 1Rx8/2Rx8/1Rx16 memory modules	Support for Extreme Memory Profile (XMP) memory modules

(Please refer "Memory Support List" for more information.)

Audio

Realtek® Audio CODEC	High Definition Audio
2/4/5.1/7.1-channel	Support for S/PDIF Out

Chipset

Intel® B660 Express Chipset

Onboard Graphics

Integrated Graphics Processor-Intel® HD Graphics support:

1 x DisplayPort, supporting a maximum resolution of 4096x2304@60 Hz * Support for DisplayPort 1.2 version and HDCP 2.3	1 x HDMI port, supporting a maximum resolution of 4096x2160@60 Hz * Support for HDMI 2.1 version and HDCP 2.3. ** Support native HDMI 2.1 TMDS compatible ports.

(Graphics specifications may vary depending on CPU support.)

LAN

Realtek® 2.5GbE LAN chip (2.5 Gbps/1 Gbps/100 Mbps)

Wireless Communication module
AMD Wi-Fi 6E RZ608 (MT7921K)

- WIFI a, b, g, n, ac, ax, supporting 2.4/5/6 GHz carrier frequency bands
- BLUETOOTH 5.2
- Support for 11ax 80MHz wireless standard and up to 1.2 Gbps data rate

(Actual data rate may vary depending on environment and equipment.)

Storage Interface
CPU:

- 1 x M.2 connector (Socket 3, M key, type 2260/2280/22110 PCIe 4.0 x4/x2 SSD support) (M2A_CPU)

Chipset:

- 1 x M.2 connector (Socket 3, M key, type 2260/2280/22110 PCIe 4.0 x4/x2 SSD support) (M2P_SB)
- 1 x M.2 connector (Socket 3, M key, type 2260/2280/22110 PCIe 3.0 x4/x2 SSD support) (M2M_SB)
- 4 x SATA 6Gb/s connectors

Support for RAID 0, RAID 1, RAID 5, and RAID 10

Intel® Optane™ Memory Ready
* System acceleration with Intel® Optane™ Memory can only be enabled on the M.2 connectors supported by the Chipset.

Internal I/O Connectors

- 1 x 24-pin ATX main power connector
- 1 x 8-pin ATX 12V power connector
- 1 x CPU fan header
- 1 x water cooling CPU fan header
- 3 x system fan headers
- 1 x system fan/water cooling pump header
- 2 x addressable LED strip headers
- 2 x RGB LED strip headers
- 3 x M.2 Socket 3 connectors
- 4 x SATA 6Gb/s connectors
- 1 x front panel header
- 1 x front panel audio header
- 1 x USB Type-C® header, with USB 3.2 Gen 2 support
- 1 x USB 3.2 Gen 1 header
- 2 x USB 2.0/1.1 headers
- 1 x Trusted Platform Module header (For the GC-TPM2.0 SPI/GC-TPM2.0 SPI 2.0 module only)
- 1 x serial port header
- 1 x Q-Flash Plus button
- 1 x reset button
- 1 x reset jumper
- 1 x Clear CMOS jumper

*All fan headers are subject to support AIO_Pump, Pump and high performance fan with the capability of delivering up to 2A/12V @ 24W.

Expansion Slots

- 1 x PCI Express x16 slot, running at x16 (PCIEX16)
  * For optimum performance, if only one PCI Express graphics card is to be installed, be sure to install it in the PCIEX16 slot. (The PCIEX16 slot conforms to PCI Express 4.0 standard.)
- 2 x PCI Express x16 slots, running at x1 (PCIEX1_1, PCIEX1_2) (All of the PCI Express slots conform to PCI Express 3.0 standard.)

USB
Chipset:

- 1 x USB Type-C® port with USB 3.2 Gen 2 support, available through the internal USB header
- 1 x USB 3.2 Gen 2 Type-A port (red) on the back panel
- 4 x USB 3.2 Gen 1 ports (2 ports on the back panel, 2 ports available through the internal USB header)
- 1 x USB 2.0/1.1 port on the back panel

Chipset+2 USB 2.0 Hubs:

- 8 x USB 2.0/1.1 ports (4 ports on the back panel, 4 ports available through the internal USB headers)

Back Panel Connectors

- 1 x USB 3.2 Gen 2 Type-A port (red)
- 2 x USB 3.2 Gen 1 ports
- 5 x USB 2.0/1.1 ports
- 1 x DisplayPort
- 1 x HDMI 2.0 port
- 1 x RJ-45 port
- 6 x audio jacks

I/O Controller

- iTE® I/O Controller Chip

BIOS

- 1 x 256 Mbit flash
- PnP 1.0a, DMI 2.7, WfM 2.0, SM BIOS 2.7, ACPI 5.0
- Use of licensed AMI UEFI BIOS

Bundled Software

- Norton® Internet Security (OEM version)
- LAN bandwidth management software

H/W Monitoring

- Voltage detection
- Temperature detection
- Fan speed detection
- Water cooling flow rate detection
- Fan fail warning
- Fan speed control * Whether the fan (pump) speed control function is supported will depend on the fan (pump) you install.

Unique Features

- Support for APP Center * Available applications in APP Center may vary by motherboard model. Supported functions of each application may also vary depending on motherboard specifications.
- @BIOS
- EasyTune
- Fast Boot
- Game Boost
- ON/OFF Charge
- RGB Fusion
- Smart Backup
- System Information Viewer
- Support for Q-Flash
- Support for Q-Flash Plus
- Support for Xpress Install

Operating System

- Support for Windows 11 64-bit
- Support for Windows 10 64-bit

Cene su informativnog karaktera. Prodavac ne odgovara za tačnost cena iskazanih na sajtu, zadržava pravo izmena cena. Ponudu za ostale artikle, informacije o stanju lagera i aktuelnim cenama možete dobiti na upit. Plaćanje se isključivo vrši virmanski - bezgotovinski.