

MB s1700 GIGABYTE Z690 UD 1.0 DDR4

Šifra: 22257
Kategorija proizvoda: Matične ploče
Proizvođač: GIGABYTE

Cena: 24.510,00



CPU		Chipset	Memory
LGA1700 socket:	L3 cache varies with CPU	Intel® Z690 Express Chipset	Supports up to 128GB DDR4-5600 (OC) memory
Support for 12th Generation Intel® Core™, Pentium® Gold and Celeron® Processors*			
* Please refer to "CPU Support List" for more information.		Onboard Graphics	Audio
		Integrated Graphics Processor-Intel® HD Graphics support:	
		1 x HDMI port, supporting a maximum resolution of 4096x2160@60 Hz	1 x DisplayPort, supporting a maximum resolution of 4096x2304@60 Hz
		* Support for HDMI 2.1 version and HDCP 2.3.	* Support for DisplayPort 1.2 version and HDCP 2.3
		** Support native HDMI 2.1 TMDS compatible ports.	
		(Graphics specifications may vary depending on CPU support.)	(Go to memory section for more details)

Realtek® Audio CODEC	High Definition Audio 2/4/5.1/7.1-channel * To configure 7.1-channel audio, you need to open the audio software and select Device advanced settings > Playback Device to change the default setting first. Please visit GIGABYTE's website for details on configuring the audio software.	LAN Realtek® 2.5GbE LAN chip (2.5 Gbps/1 Gbps/100 Mbps)	Expans 1 x P runni * For perfo PCI E card be su PCIEX (The confo 5.0 st
		Multi-Graphics Technology Support for AMD Quad-GPU CrossFire™ and 2-Way AMD CrossFire™ technologies	Storag CPU: 1 x M (Sock 2260, 4.0 x (M2A Chipse 1 x M (Sock 2260, x4/x2 (M2P
		USB Chipset: 1 x USB Type-C® port on the back panel, with USB 3.2 Gen 2x2 support	Support Intern 1 x 2 Intel® * Powe System can on by the
			1 x USB Type-C® port with USB 3.2 Gen 1 support, available through the internal USB header 1 x USB 3.2 Gen 2 type-A ports (red) on the back panel 6 x USB 3.2 Gen 1 ports (4 ports on the back panel, 2 ports available through the internal USB header)
		Chipset+2 USB 2.0 Hubs: 8 x USB 2.0/1.1 ports (4 ports on the back panel, 4 ports available through the internal USB headers)	

