

MB s1700 Gigabyte B660M GAMING X DDR4

Šifra: 22267

Kategorija proizvoda: Matične ploče

Proizvođač: GIGABYTE

Cena: **19.190,00**



CPU

LGA1700 socket: L3 cache varies with CPU
Support for 12th Generation Intel® Core™, Pentium® Gold and Celeron® Processors*

* Please refer to "CPU Support List" for more information.

Chipset

Intel® B660 Express Chipset

Onboard Graphics

Integrated Graphics Processor-Intel® HD Graphics support:

1 x HDMI port, supporting a maximum resolution of 4096x2160@60 Hz
* Support for HDMI 2.1 version and HDCP 2.3.
** Support native HDMI 2.1 TMDS compatible ports.

1 x DisplayPort, supporting a maximum resolution of 4096x2304@60 Hz
* Support for DisplayPort 1.2 version and HDCP 2.3

(Graphics specifications may vary depending on CPU support.)

Memor
Supp
4400
4300
4133
3866
3733
3600
3400
3300
/3200
MHz

Audio

(Please
informa

Realtek® Audio CODEC

High Definition Audio
2/4/5.1/7.1-channel
*To configure 7.1-
Support for SPDIF Out
channel audio, you need
to open the audio
software and select
Device advanced
settings > Playback
Device to change the
default setting first.
Please visit GIGABYTE's
website for details on
configuring the audio
software.

LAN

2.5GbE LAN chip (2.5
Gbps/1 Gbps/100 Mbps)

Expans
1 x P
runni
* For
perfo
PCI E
card
be su
PCIEX
(The
confo
4.0 st

Multi-Graphics Technology

Support for AMD Quad-
GPU CrossFire™ and 2-
Way AMD CrossFire™
technologies

Storag
CPU:
1 x M
(Sock
2260,
x4/x2
(M2A
Chipse
1 x M
(Sock
2260,
4.0 x
(M2P

USB

Chipset:

1 x USB Type-C® port
with USB 3.2 Gen 2
support, available
through the internal USB
header

5 x USB 3.2 Gen 1 ports
(3 ports on the back
panel, 2 ports available
through the internal USB
header)

1 x USB 2.0/1.1 port on
the back panel

Support
Intel®
* Syste
1 x 2
can on
power
by the

Chipset+2 USB 2.0 Hubs:

8 x USB 2.0/1.1 ports (4
ports on the back panel,
4 ports available
through the internal USB
headers)

only)

1 x serial port header
1 x reset button
1 x Q-Flash Plus button
1 x reset jumper
1 x Clear CMOS jumper

Back Panel Connectors
3 x USB 3.2 Gen 1 ports

5 x USB 2.0/1.1 ports
1 x HDMI 2.1 port
1 x DisplayPort
1 x RJ-45 port
3 x audio jacks

I/O Con
iTE®

*All fan headers are subject to support AIO_Pump, Pump and high performance fan with the capability of delivering up to 2A/12V @ 24W.

H/W Monitoring
Voltage detection

Temperature detection
Fan speed detection
Fan fail warning
Fan speed control
* Whether the fan speed control function is supported will depend on the fan you install.

BIOS
1 x 2

Unique Features

Support for APP Center
* Available applications in APP Center may vary by motherboard model. Supported functions of each application may also vary depending on motherboard specifications.
@BIOS
EasyTune
Fast Boot
Game Boost
ON/OFF Charge
RGB Fusion
Smart Backup
System Information Viewer

Support for Q-Flash Plus

Bundle
Norto
Secur

Support for Q-Flash
Support for Xpress Install

Operating System

Support for Windows 11
64-bit

Support for Windows 10
64-bit

Form F
Micro
24.4c