

MB s1700 GIGABYTE PRIME H610M S2H

Šifra: 22295
Kategorija proizvoda: Matične ploče
Proizvođač: GIGABYTE

Cena: 10.990,00



CPU
LGA1700 socket: L3 cache varies with CPU
Support for 12th Generation Intel® Core™, Pentium® Gold and Celeron® Processors*

* Please refer to "CPU Support List" for more information.

Chipset
Intel® H610 Express Chipset

Memor
Supp
3200
MHz

Onboard Graphics
Integrated Graphics Processor-Intel® HD Graphics support:

1 x D-Sub port,
supporting a maximum
resolution of
1920x1200@60 Hz

1 x DVI-D port,
supporting a maximum
resolution of
1920x1200@60 Hz

* The DVI-D port does
not support D-Sub
connection by adapter.
1 x HDMI port,
supporting a maximum
resolution of
4096x2160@60 Hz

* Support for HDMI 2.1
version and HDCP 2.3.
** Support native HDMI
2.1 TMDS compatible
ports

1 x DisplayPort,
supporting a maximum
resolution of
4096x2304@60 Hz

* Support for DisplayPort
1.2 version and HDCP 2.3

Audio

(Please
informa

(Graphics specifications may vary depending on CPU support.)

Realtek® Audio CODEC	High Definition Audio 2/4/5.1/7.1-channel * To configure 7.1-channel audio, you need to open the audio software and select Device advanced settings > Playback Device to change the default setting first. Please visit GIGABYTE's website for details on configuring the audio software.	LAN Realtek® GbE LAN chip (1 Gbps/100 Mbps)	Expansion Slots 1 x PCIe 4.0 x16 slot (For running graphics card) * For better performance, please use a PCIe 4.0 x16 slot (The slot color is blue). Express
		Storage Interface Chipset: 1 x M.2 connector (Socket 3, M key, type 2260/2280 PCIe 3.0 x4/x2 SSD support)	USB Chipset 4 x USB 3.2 Gen 1 (2 ports on the rear panel, 2 through the front panel)
			Chipset 4 x USB 2.0 (4 available internal headers)
		Internal I/O Connectors 1 x 24-pin ATX main power connector	Back Panel I/O 1 x 8-pin ATX 12V power connector 1 x M.2 Socket 3 connector 4 x SATA 6Gb/s connectors 1 x CPU fan header 2 x system fan headers 1 x RGB LED strip header 1 x front panel header 1 x front panel audio header 1 x USB 3.2 Gen 1 header 2 x USB 2.0/1.1 headers 1 x Trusted Platform Module header (For the GC-TPM2.0 SPI/GC-TPM2.0 SPI 2.0 module only) 1 x Clear CMOS jumper

1 x PS/2 keyboard port	1 x PS/2 mouse port	I/O Controller iTE® I/O Controller Chip	H/W M
	1 x D-Sub port		Volta
	1 x DVI-D port		
	1 x DisplayPort		
	1 x HDMI 2.0 port		
	2 x USB 3.2 Gen 1 ports		
	4 x USB 2.0/1.1 ports		
	1 x RJ-45 port		
	3 x audio jacks		
		BIOS 1 x 256 Mbit flash	Unique
		Use of licensed AMI UEFI BIOS PnP 1.0a, DMI 2.7, WfM 2.0, SM BIOS 2.7, ACPI 5.0	Supp * Ava in AP by m Supp each also v moth speci ©BIO Ambi Easy7 Operat Fast 1 Supp ON/O Smar Syste Viewe
		Bundled Software Norton® Internet Security (OEM version)	LAN bandwidth management software
		Form Factor Micro ATX Form Factor; 23.0cm x 21.5cm	

Cene su informativnog karaktera. Prodavac ne odgovara za tačnost cena iskazanih na sajtu, zadržava pravo izmena cena. Ponudu za ostale artikle, informacije o stanju lagera i aktuelnim cenama možete dobiti na upit. Plaćanje se isključivo vrši virmanski - bezgotovinski.