

## MB AM4 Gigabyte B450M DS3H V2 1.2

Šifra: 28853

Kategorija prozivoda: Matične ploče

Proizvođač: GIGABYTE

Cena: **9.063,00**



### CPU

AM4 Socket: Supports  
AMD Ryzen™ 5000  
series / Ryzen™ 5000 G-  
Series/ 3rd Gen Ryzen™ /  
2nd Gen Ryzen™ / 1st  
Gen Ryzen™ / 2nd Gen  
Ryzen™ with Radeon™  
Vega Graphics/ 1st Gen  
Ryzen™ with Radeon™  
Vega Graphics/ Athlon™  
with Radeon™ Vega  
Graphics Processors

(Please refer "CPU Support List" for more information.)

### Chipset

AMD B450

### Memor

4 x D  
suppo  
(32 G  
capac  
mem

### Onboard Graphics

#### Integrated Graphics Processor:

1 x DVI-D port,  
supporting a maximum  
resolution of  
1920x1200@60 Hz  
\* The DVI-D port does  
not support D-Sub  
connection by adapter.

1 x HDMI port,  
supporting a maximum  
resolution of  
4096x2160@60 Hz (Note)  
\* Support for HDMI 2.0  
version and HDCP 2.2.  
(Note)

### Audio

(Please  
informa

Maximum shared memory of 16 GB

(Note) Actual support may vary by CPU.

## Realtek® Audio codec

High Definition Audio  
2/4/5.1/7.1-channel  
To configure 7.1 channel  
audio, you need to open  
the audio software and  
select Device advanced  
settings > Playback  
Device to change the  
default setting first.  
Please visit GIGABYTE's  
website for details on  
configuring the audio  
software.

## LAN

Realtek® GbE LAN chip  
(10/100/1000 Mbit)

Expans  
1 x Pe  
runni  
(Note  
\* For  
perfo  
PCI E  
card  
be su  
PCIEX  
(The  
confco  
3.0 st

## Multi-Graphics Technology

Support for AMD Quad-  
GPU CrossFire™ and 2-  
Way AMD CrossFire™  
technologies

Storage  
1 x M  
(Sock  
2242,  
SATA  
(Note  
SSD s  
\* Actu  
vary  
\* Sup  
SATA  
an AM  
7th G  
Athlo

## USB

### Chipset:

2 x USB 3.1 Gen 1 ports  
available through the  
internal USB header

Internat

8 x USB 2.0/1.1 ports (4  
ports on the back panel,  
4 ports available  
through the internal USB  
headers)

## CPU:

4 x USB 3.1 Gen 1 ports  
on the back panel

1 x 24-pin ATX main power connector	1 x 8-pin ATX 12V power connector	Back Panel Connectors	I/O Connectors
	1 x CPU fan header	1 x PS/2 keyboard/mouse port	1 x DVI-D port
	1 x system fan header		1 x HDMI port
	1 x M.2 Socket 3 connector		4 x USB 3.1 Gen 1 ports
	40x SATA 6Gb/s connectors		4 x USB 2.0/1.1 ports
	1 x front panel header		1 x RJ-45 port
	1 x front panel audio header		3 x audio jacks
	1 x S/PDIF Out header		
	1 x CPU cooler LED strip/RGB LED strip header		
	2 x USB 2.0/1.1 headers		
	1 x Trusted Platform Module (TPM) header		
	1 x serial port header (2x10 pin, for the GC-TPM2.0 module only)		
	1 x Clear CMOS jumper		
		H/W Monitoring	BIOS
		Voltage detection	1 x 1
		Temperature detection	
		Fan speed detection	
		Overheating warning	
		Fan fail warning	
		Fan speed control	
		* Whether the fan speed control function is supported will depend on the cooler you install.	
		Unique Features	Bundle
		Support for APP Center * Available applications in APP Center may vary by motherboard model. Supported functions of each application may also vary depending on motherboard specifications. @BIOS EasyTune Fast Boot ON/OFF Charge RGB Fusion Smart Backup System Information Viewer	Norton Security
		Support for Q-Flash	
		Support for Xpress Install	
		Operating System	Form Factor
		Support for Windows 11 64-bit	
		Support for Windows 10 64-bit	

Micro ATX Form Factor;  
24.4cm x 21.5cm

Remark

Due to different Linux support condition provided by chipset vendors, please download Linux driver from chipset vendors' website or 3rd party website.

Most hardware/software vendors may no longer offer drivers to support Win9X/ME/2000/XP. If drivers are available from the vendors, we will update them on the GIGABYTE website.