

Cudy GS1020PS2 16-Port Gigabit PoE+ Switch with 2 Gigabit SFP ports 200W

Šifra: 29429
Kategorija proizvoda: Mrežna oprema
Proizvođač: CUDY



Cena: 16.540,00

- IEEE 802.3af / 802.3at standard compliant
- 200-watt total PoE power budget, up to 30-watt per port
- 16xGbE PoE+Port+2xSFP/GbE Combo Port
- CCTV Mode supports remote power&data feeding up to 250M
- VLAN mode supports 16 POE+ ports isolated from each other
- LED indicators for network diagnostics
- 19-inch metal case, internal power design

Connector Type: 16*10/100/1000M PoE Ports + 2*Gigabit SFP Uplink Ports

Network Media (Cable):

IEEE802.3
IEEE802.3u
IEEE802.3x
IEEE802.3ab
IEEE802.3z

PoE Parameters:

PoE Standard: IEEE802.3af /IEEE802.3at

Max each port: 15.4W (IEEE 802.3af)

Max each port:30W (IEEE 802.3at)

PoE compatibility: IEEE 802.3af/at adaptive

PoE port output: DC48-55V

Power Pin : Power over spare pairs 1/2(+) , 3/6 (-)

Network Media:

10BASE-T: Cat 5E UTP(=250 meter)

100BASE-TX: Cat5 or more UTP (=100 meter)

1000BASE-TX: Cat5 or more UTP (=100 meter)

Optical:

-MultiMode Fiber: 850nm, 1310nm, Transmission Distance: 550m/2Km

-Single-Mode Fiber: 1310nm, 1550nm, Transmission Distance: 20/40/60/80/100/120km

Performance Specification:

Bandwidth: 52Gbps

MAC: 8K

Packet Buffer Memory: 4M

Packet Forwarding Rate: 38.7Mpps

Power Supply Power input: AC100-240V 50/60Hz, Output: 52V3.85A, Power Budget: 200W

PWR

Power supply indicator (Red)

Lighting:Powered

Un-Light:No Power

1-26

RJ-45 LINK indicator (Green)

Lighting:1000M Connect

Un-Light:100M or Disconnect

1-26

RJ-45 ACT indicator (Green)

Lighting:Connecting

Flashing:Data Transmit

Un-Light:Disconnect