Firma: PC COOL DOO
Adresa: Višegradska 26A
Telefon: 0653526116
Fax:
PIB: 104045201
E-mail: info@pccool.rs

SVGA Radeon RX6750 XT Sapphire Pulse Gaming OC 12GB, 11318-03-20G



Šifra: 30517
Kategorija prozivoda: Grafičke kartice
Proizvođač: SAPPHIRE

Cena: 51.890,00

Specifications

#SKU#: 11318-03-20G SAPPHIRE PULSE AMD Radeon™ RX 6750 XT, 12GB, AMD RDNA™ 2

GPU
AMD Radeon™ RX 6750 XT Graphics Card
7nm GPU
AMD RDNA™ 2 Architecture

Engine Clock
Boost Clock: Up to 2618 MHz
Game Clock: Up to 2512 MHz

Boost Clock is the maximum frequency achievable on the GPU running bursty workload. Boost clock achievability, frequency, and sustainabilty will vary based on several factors, including but not limited to: thermal conditions and variation in application and workloads.

Game Clock is the expected GPU clock when running typical gaming applications, set to typical TGP(Total Graphics Power). Actual individual game clock results may vary.

Stream Processors
2560

Infinity Cache
96MB

Ray Accelerators
40

Memory Size/Bus
12GB GDDR6

Memory Clock
18 Gbps Effective

Displays
Maximum 4 Displays

Resolution
HDMI™: 7680×4320
DisplayPort1.4: 7680×4320

Interface
PCI-Express 4.0 x16

Output
1x HDMI
3x DisplayPort

HIGH-DEFINITION MULTIMEDIA INTERFACE

BIOS Support
UEFI

Game Index
1440P

Sapphire Features
Premium Digital Power Design
Fuse Protection
High TG Copper PCB
Optimized Composite Heatpipe
Dual-X Cooling Technology
Intelligent Fan Control
Precision Fan Control
Metal Backplate with Thermal Pad

Two-Ball Bearing Fans	TriXX Supported
TriXX Boost	

AMD Features

AMD RDNA™ 2 Gaming Architecture	DirectX® 12 Ultimate
Hardware Raytracing	GDDR6 Memory
Smart Access Memory	Infinity Cache
7nm GPU	PCI® Express 4.0 Support
AMD FreeSync™ Technology	DisplayPort™ 1.4 with DSC
HDMI™	Video Streaming up to 8K
Radeon™ VR Ready Premium	AMD FidelityFX
AMD FidelityFX™ Super Resolution (FSR)	AMD Radeon™ Super Resolution
Radeon™ Image Sharpening	Radeon™ Anti-Lag
Radeon™ Software	Game Driver Optimizations

Cooling

Dual Fans

Form Factor

2.7 slot, ATX

Dimension: 280(L)X 122.75(W)X 50.47(H)mm

Power Consumption

250W Total Board Power

OS

Linux®, Windows® 7*, Windows® 10, and Windows 11. 64-bit operating system required

*Does not support all features including but not limited to Hardware Raytracing

System Requirement

Minimum 650 Watt Power Supply	1 x 8-pin + 1 x 6-pin Power Connector

Cene su informativnog karaktera. Prodavac ne odgovara za tačnost cena iskazanih na sajtu, zadržava pravo izmena cena. Ponudu za ostale artikle, informacije o stanju lagera i aktuelnim cenama možete dobiti na upit. Plaćanje se isključivo vrši virmanski - bezgotovinski.