

MB AM4 GIGABYTE B550M DS3H

Šifra: 30980

Kategorija proizvoda: Matične ploče

Proizvođač: GIGABYTE

Cena: **11.910,00**



CPU

AMD Socket AM4,
support for: AMD
Ryzen™ 5000 Series/
Ryzen™ 5000 G-Series/
Ryzen™ 4000 G-Series
and Ryzen™ 3000 Series
Processors

(Please refer "CPU Support List" for more information.)

Chipset

AMD B550

Memor

4 x D
suppo
(32 G
capac
mem

Onboard Graphics

Integrated Graphics Processor:

1 x DVI-D port,
supporting a maximum
resolution of
1920x1200@60 Hz
* The DVI-D port does
not support D-Sub
connection by adapter.

1 x HDMI port,
supporting a maximum
resolution of
4096x2160@60 Hz
* Support for HDMI 2.1
version, HDCP 2.3, and
HDR.

Audio

Maximum shared memory of 16 GB

(Please
informa

Realtek® Audio CODEC

High Definition Audio

2/4/5.1/7.1-channel

* To configure 7.1-channel audio, you need to open the audio software and select Device advanced settings > Playback Device to change the default setting first. Please visit GIGABYTE's website for details on configuring the audio software.

LAN

Realtek® GbE LAN chip
(1000 Mbit/100 Mbit)

Expans

1 x PCI
CPU:
AMD
Serie
Serie
suppo
mode

Storage Interface

1 x M.2 connector (M2A_CPU), integrated in the CPU, supporting Socket 3, M key, type 2242/2260/2280/22110 SSDs:

AMD Ryzen™ 5000 Series and Ryzen™ 3000 Series Processors support SATA and PCIe 4.0 x4/x2 SSDs

AMD Ryzen™ Ryzen™ 5000 G-Series and Ryzen™ 4000 G-Series Processors support SATA and PCIe 3.0 x4/x2 SSDs

USB

CPU:
4 x U
on th
1 x PCI
Chipse
2 x U
Supp
avail
mode
intern
1 x PCI
Chipse
Supp
mode

1 x M.2 connector (M2B_SB), integrated in the Chipset, supporting Socket 3, M key, type 2242/2260/2280 SSDs:

Supporting SATA and PCIe 3.0 x2 SSDs

4 x SATA 6Gb/s connectors, integrated in the Chipset:
Support for RAID 0, RAID 1, and RAID 10

Internal I/O Connectors

1 x 24-pin ATX main power connector

1 x 8-pin ATX 12V power connector

1 x CPU fan header

2 x system fan headers

2 x addressable LED

strip headers

2 x RGB LED strip

headers

1 x CPU cooler LED

strip/RGB LED strip

header

2 x M.2 Socket 3

connectors

4 x SATA 6Gb/s

connectors

1 x front panel header

1 x front panel audio

header

1 x USB 3.2 Gen 1

header

1 x USB 2.0/1.1 header

1 x Trusted Platform

Module (TPM) header (2x6 pin, for the GC-TPM2.0_S module only)	1 x serial port header	Back Panel Connectors 1 x PS/2 keyboard/mouse port	1 x DVI-D port	I/O Controller iTE®
	1 x Clear CMOS jumper 1 x Q-Flash Plus button		1 x HDMI port 4 x USB 3.2 Gen 1 ports 4 x USB 2.0/1.1 ports 1 x RJ-45 port 3 x audio jacks	
*All fan headers are subject to support AIO_Pump, Pump and high performance fan with the capability of delivering up to 2A/12V @ 24W.				
		H/W Monitoring Voltage detection	Temperature detection Fan speed detection Overheating warning Fan fail warning Fan speed control * Whether the fan speed control function is supported will depend on the cooler you install.	BIOS 1 x 2
		Unique Features Support for APP Center * Available applications in APP Center may vary by motherboard model. Supported functions of each application may also vary depending on motherboard specifications. @BIOS EasyTune Fast Boot Game Boost ON/OFF Charge RGB Fusion Smart Backup System Information Viewer	Support for Q-Flash Plus	Bundle Norton Security
			Support for Q-Flash Support for Xpress Install	
		Operating System Support for Windows 10 64-bit		Form Factor Micro 24.4cm