Firma: PC COOL DOO
Adresa: Višegradska 26A
Telefon: 0653526116
Fax:
PIB: 104045201
E-mail: info@pccool.rs

MB AM5 Biostar B650EGTQ 2xDDR5M.2HDMIDP

Šifra: 31128
Kategorija prozivoda: Matične ploče
Proizvođač: Nedefinisan1

Cena: 29.300,00



Procesorsko podnožje (Socket)	AMD Socket AM5
Skup čipova (Chipset)	AMD B650
Podrška za procesore	AMD Socket AM5 for AMD Ryzen™ 7000 Series Desktop Processors
Tip memorije (RAM)	DDR5
Broj memorijskih slotova	4x 288-Pin DDR5
Podrška za memorije	4 x DIMM, Max. 128GB, DDR5 6400+(OC)/6200(OC)/ 6000(OC)/ 5800(OC)/ 5600(OC)/ 5400(OC)/ 5200/ 5000/ 4800 ECC andNon-ECC, Un-buffered Memory Dual Channel Memory Architecture Supports AMD EXTended Profiles for Overclocking (EXPO™) OptiMem II Supported memory types, data rate(Speed), and number of DRAM module vary depending on the CPU and memory configuration, for more information refer to www.asus.com for memory support list. Non-ECC, Un-buffered DDR5 Memory supports On-Die ECC function
Podrška za grafiku - portovi	1 x DisplayPort 1 x HDMI® port Supports max. 8K@60Hz as specified in DisplayPort 1.4. Supports max. 4K@60Hz as specified in HDMI 2.1.
Slotovi za proširenja	AMD Ryzen™ 7000 Series Desktop Processors 2 x PCIe 5.0 x16 slots (supports x16 & x8/x4 modes) AMD B650 Chipset 1 x PCIe 4.0 x16 slot (supports x4 mode)
M.2 portovi	4x M.2 Socket 3
Čuvanje podataka - portovi	AMD Ryzen™ 7000 Series Desktop Processors M.2_1 slot (Key M), type 2242/2260/2280 (supports PCIe 5.0 x4 mode) M.2_2 slot (Key M), type 2242/2260/2280 (supports PCIe 4.0 x4 mode) M.2_3 slot (Key M), type 2242/2260/2280/22110 (supports PCIe 5.0 x4 mode) AMD X670 Chipset M.2_4 slot (Key M), type 2242/2260/2280 (supports PCIe 4.0 x4 mode) 4 x SATA 6Gb/s ports AMD RAIDXpert2 Technology supports both PCIe RAID 0/1/10 and SATA RAID 0/1/10.
U.2 portovi	nema
SATA Express portovi	nema
SATA portovi	4x SATA 6Gb/s

LAN	1 x Intel® 2.5Gb Ethernet ASUS LANGuard
Bežična mreža	Wi-Fi 6E 2x2 Wi-Fi 6E (802.11 a/b/g/n/ac/ax) Supports 2.4/5/6GHz frequency band
Bluetooth	Bluetooth v5.2
Zvuk (Audio)	ROG SupremeFX 7.1 Surround Sound High Definition Audio CODEC ALC4080 - Impedance sense for front and rear headphone outputs - Supports: Jack-detection, Multi-streaming, Front Panel Jack-retasking - High quality 120 dB SNR stereo playback output and 113 dB SNR recording input - Supports up to 32-Bit/384 kHz playback" Audio Features - Audio Shielding - Savitech SV3H712 AMP - Rear optical S/PDIF out port - Premium audio capacitors - Audio cover
USB portovi	Rear USB (Total 12 ports) 1 x USB 3.2 Gen 2x2 port (1 x USB Type-C®) 7 x USB 3.2 Gen 2 ports (6 x Type-A + 1 x USB Type-C®) 4 x USB 2.0 ports Front USB (Total 7 ports) 1 x USB 3.2 Gen 2 connector (supports USB Type-C®) 1 x USB 3.2 Gen 1 header supports additional 2 USB 3.2 Gen 1 ports 2 x USB 2.0 headers support additional 4 USB 2.0 ports
Konektori na zadnjoj strani	1 x USB 3.2 Gen 2x2 port (1 x Type-C®) 7 x USB 3.2 Gen 2 ports (6 x Type-A, 1 xUSB Type-C®) 4 x USB 2.0 ports 1 x DisplayPort 1 x HDMI® port 1 x Wi-Fi Module 1 x Intel® 2.5Gb Ethernet port 5 x Audio jacks* 1 x Optical S/PDIF out port 1 x BIOS FlashBack™ button 1 x Clear CMOS button
Unutrašnji konektori	Fan and Cooling related 1 x 4-pin CPU Fan header 1 x 4-pin CPU OPT Fan header 1 x 4-pin AIO Pump header 5 x 4-pin Chassis Fan headers Power related 1 x 24-pin Main Power connector 2 x 8-pin +12V Power connector Storage related 4 x M.2 slots (Key M) 4 x SATA 6Gb/s ports USB 1 x USB 3.2 Gen 2 connector (supports USB Type-C®) 1 x USB 3.2 Gen 1 header supports additional 2 USB 3.2 Gen 1 ports 2 x USB 2.0 headers support additional 4 USB 2.0 ports Miscellaneous 3 x Addressable Gen 2 headers 1 x Aura RGB header 1 x CPU Over Voltage jumper 1 x Front Panel Audio header (AAFP) 1 x 20-3 pin System Panel header with Chassis intrude function 1 x Thermal Sensor header 1 x Thunderbolt™ (USB4®) header
Posebne mogućnosti	Extreme Engine Digi+ - 5K Black Metallic Capacitors ASUS Q-Design - M.2 Q-Latch - PCIe Slot Q-Release - Q-DIMM - Q-LED (CPU [red], DRAM [yellow], VGA

	[white], Boot Device [yellow̆ green]) - Q-Slot ASUS Thermal Solution - M.2 heatsinks - M.2 heatsink backplate - VRM heatsink design ASUS EZ DIY - BIOS FlashBack™ button - BIOS FlashBack™ LED - Clear CMOS button - ProCool - Pre-mounted I/O shield - SafeSlot - SafeDIMM Aura Sync - Aura RGB header - Addressable Gen 2 headers
Operativni sistem	Windows® 10; Windows® 11
BIOS	256 Mb Flash ROM, UEFI AMI BIOS
Format	ATX
Dodatna oprema	Cables 2 x SATA 6Gb/s cables Additional Cooling Kit 1 x Thermal pad for M.2 Miscellaneous 1 x ASUS Wi-Fi moving antennas 1 x Cable ties pack 1 x M.2 Q-Latch package 1 x ROG key chain 1 x ROG Strix stickers 1 x ROG Strix thank you card 2 x Rubber Packages for M.2

Cene su informativnog karaktera. Prodavac ne odgovara za tačnost cena iskazanih na sajtu, zadržava pravo izmena cena. Ponudu za ostale artikle, informacije o stanju lagera i aktuelnim cenama možete dobiti na upit. Plaćanje se isključivo vrši virmanski - bezgotovinski.