

logo image not found or type unknown

Firma: PC COOL DOO
Adresa: Višegradska 26A
Telefon: 0653526116
Fax:
PIB: 104045201
E-mail: info@pccool.rs

MB Gigabyte s1700 B660M DS3H DDR4

Šifra: 31142
Kategorija proizvoda: Matične ploče
Proizvođač: GIGABYTE

Cena: **14.260,00**



CPU

LGA1700 socket: L3 cache varies with CPU
Support for 12th
Generation Intel®
Core™, Pentium® Gold
and Celeron®
Processors*

Chipset

Intel® B660 Express
Chipset

Memor

* Please refer to "CPU Support List" for more
information.

Support for DDR4 5333(O.C.)/ DDR4 5133(O.C.)/DDR4 5000(O.C.)/4933(O.C.)/4800(O.C.)/ 4700(O.C.)/ 4600(O.C.)/ 4500(O.C.)/ 4400(O.C.)/ 4300(O.C.)/4266(O.C.) / 4133(O.C.) / 4000(O.C.) / 3866(O.C.) / 3800(O.C.) / 3733(O.C.) / 3666(O.C.) / 3600(O.C.) / 3466(O.C.) / 3400(O.C.) / 3333(O.C.) / 3300(O.C.) / 3200/3000/2933/2666/2400/2133 MHz memory modules	4 x DDR DIMM sockets supporting up to 128 GB (32 GB single DIMM capacity) of system memory	Onboard Graphics Integrated Graphics Processor-Intel® HD Graphics support:	Audio Realtek
	Dual channel memory architecture	1 x D-Sub port, supporting a maximum resolution of 1920x1200@60 Hz	1 x HDMI port, supporting a maximum resolution of 4096x2160@60 Hz * Support for HDMI 2.1 version and HDCP 2.3 ** Support native HDMI resolution of 4096x2304@60 Hz Ports: 1 x DisplayPort, supporting a maximum resolution of 4096x2304@60 Hz * Support for DisplayPort 1.2 version and HDCP 2.3
	Support for ECC Un-buffered DIMM 1Rx8/2Rx8 memory modules (operate in non-ECC mode)		1 x DisplayPort, supporting a maximum resolution of 4096x2304@60 Hz * Support for DisplayPort 1.2 version.
	Support for Extreme Memory Profile (XMP) memory modules	(Graphics specifications may vary depending on CPU support.)	
		Support for up to 4 displays at the same time	
(Please refer "Memory Support List" for more information.)			
		LAN Realtek® 2.5GbE LAN chip (2.5 Gbps/1 Gbps/100 Mbps)	Expansion 1 x PCI Express® 4.0 slots
		Storage Interface CPU: 1 x M.2 connector (Socket 3, M key, type 2260/2280 PCIe 4.0 x4/x2 SSD support) (M2A_CPU) Chipset: 1 x M.2 connector (Socket 3, M key, type 2260/2280 PCIe 4.0 x4/x2 SSD support) (M2P_SB)	
			4 x SATA 6Gb/s connectors
		Support for RAID 0, RAID 1, RAID 5, and RAID 10	
		Intel® Optane™ Memory Ready * System acceleration with Intel® Optane™ Memory can only be enabled on the M.2 connector supported by	

the Chipset.

USB

Interna

Chipset:

1 x 24
power

1 x USB Type-C® port on the back panel, with USB 3.2 Gen 2 support

5 x USB 3.2 Gen 1 ports
(3 ports on the back
panel, 2 ports available
through the internal USB
header)
2 x USB 2.0/1.1 ports on
the back panel

Chipset+2 USB 2.0 Hubs:

4 x USB 2.0/1.1 ports
available through the
internal USB headers

Back Panel Connectors

2 x USB 2.0/1.1 ports

1 x PS/2
keyboard/mouse port
1 x D-Sub port

I/O Cor
iTE®

- 1 x HDMI port
- 2 x DisplayPorts
- 3 x USB 3.2 Gen 1 ports
- 1 x USB Type-C® port,
with USB 3.2 Gen 2
support

3 x audio jacks

*All far
and hig
deliver

H/W Monitoring

Voltage detection

BIOS

- Temperature detection
- Fan speed detection
- Fan fail warning
- Fan speed control
- * Whether the fan speed control function is supported will depend on the cooler you install.

1 x 256 Mbit flash	Use of licensed AMI UEFI BIOS PCI 1.0a, DMI 2.7, WfM 2.0, SM BIOS 2.7, ACPI 5.0	Unique Features Support for APP Center * Available applications in APP Center may vary by motherboard model. Supported functions of each application may also vary depending on motherboard specifications. @BIOS EasyTune Fast Boot Game Boost ON/OFF Charge RGB Fusion Smart Backup System Information Viewer	Support for Q-Flash Plus	Bundle Norton Security
			Support for Q-Flash Support for Xpress Install	
		Operating System Support for Windows 11 64-bit	Support for Windows 10 64-bit	Form Factor Micro ATX