

logo not found or type unknown

Firma: PC COOL DOO
Adresa: Višegradska 26A
Telefon: 0653526116
Fax:
PIB: 104045201
E-mail: info@pccool.rs

MB Gigabyte AMD AM4 A520M DS3H

Šifra: 31143

Kategorija proizvoda: Matične ploče

Proizvođač: GIGABYTE

Cena: **8.440,00**



CPU

AMD Socket AM4,
support for: AMD
Ryzen™ 5000 Series/
Ryzen™ 5000 G-Series/
Ryzen™ 4000 G-Series
and Ryzen™ 3000 Series
Processors

(Please refer "CPU Support List" for more information.)

Chipset

AMD A520

Memor

4 x DDR4 DIMM sockets supporting up to 128 GB (32 GB single DIMM capacity) of system memory	AMD Ryzen™ 5000 G-series / Ryzen™ 5000 Series/ 3rd Generation AMD Ryzen™ processors: Support for DDR4 4400(O.C.) / 4000(O.C.) / 3866(O.C.) / 3800(O.C.) / 3733(O.C.) / 3600(O.C.) / 3466(O.C.) / 3400(O.C.) / 3333(O.C.) / 3200(O.C.) / 2400(O.C.) / 2133 MHz memory modules Dual channel memory architecture	Onboard Graphics Integrated in the 3rd Generation AMD Ryzen™ with Radeon™ Graphics processors: 1 x DVI-D port, supporting a maximum resolution of 1920x1200@60 Hz * The DVI-D port does not support D-Sub connection by adapter.	1 x DisplayPort, supporting a maximum resolution of 5120x2880@60 Hz * Support for DisplayPort 1.4 version, HDCP 2.3, and HDR. 1 x HDMI port, supporting a maximum resolution of 4096x2160@60 Hz * Support for HDMI 2.1 version, HDCP 2.3, and HDR.	Audio Realtek
	Support for ECC Unbuffered DIMM 1Rx8/2Rx8 memory modules Support for non-ECC Unbuffered DIMM 1Rx8/2Rx8/1Rx16 memory modules Support for Extreme Memory Profile (XMP) memory modules	Support for up to 3 displays at the same time Maximum shared memory of 16 GB		
(Please refer "Memory Support List" for more information.)		LAN Realtek® GbE LAN chip (1000 Mbit/100 Mbit)		Expansion CPU: 1 x PCIe support running Chipset: 2 x PCIe support (PCIe
		Storage Interface CPU: 1 x M.2 connector (Socket 3, M key, type 2242/2260/2280 SATA and PCIe 3.0 x4/x2 SSD support) Chipset: 4 x SATA 6Gb/s		

connectors	Support for RAID 0, RAID 1, and RAID 10	USB CPU: 4 x USB 3.2 Gen 1 ports on the back panel Chipset: 2 x USB 3.2 Gen 1 ports available through the internal USB header	4 x USB 2.0/1.1 ports (2 ports on the back panel, 2 ports available through the internal USB header)	Internal 1 x 2 power
		Back Panel Connectors 1 x PS/2 keyboard/mouse port	1 x DVI-D port 1 x DisplayPort 1 x HDMI port 4 x USB 3.2 Gen 1 ports 2 x USB 2.0/1.1 ports 1 x RJ-45 port 3 x audio jacks	I/O Con iTE®
				*All fan and high deliver
		H/W Monitoring Voltage detection	Temperature detection Fan speed detection Overheating warning Fan fail warning Fan speed control * Whether the fan speed control function is supported will depend on the cooler you install.	BIOS 1 x 1
		Unique Features Support for APP Center * Available applications in APP Center may vary by motherboard model. Supported functions of each application may also vary depending on motherboard specifications.		

@BIOS
EasyTune
Fast Boot
Game Boost
ON/OFF Charge
RGB Fusion
Smart Backup
System Information
Viewer

Support for Q-Flash Plus

Support for Q-Flash
Support for Xpress Install

Bundled Software
Norton® Internet
Security (OEM version)

Form Factor
Micro ATX Form Factor;
24.4cm x 24.4cm

Realtek® 8118 Gaming
LAN Bandwidth Control
Utility

Operat
Supp
64-bi