Firma: PC COOL DOO
Adresa: Višegradska 26A
Telefon: 0653526116
Fax:
PIB: 104045201
E-mail: info@pccool.rs

# MB s1700 Gigabyte H610M S2H DDR4 G10

Šifra: 33425
Kategorija prozivoda: Matične ploče
Proizvođač: GIGABYTE

## Cena: 11.360,00




CPU

| | |
|---|---|
| LGA1700 socket: Support for 12th Generation Intel® Core™, Pentium® Gold and Celeron® Processors* | L3 cache varies with CPU |

* Please refer to "CPU Support List" for more information.

Chipset

| | |
|---|---|
| Intel® H610 Express Chipset | |

Memory

| | |
|---|---|
| Support for DDR4 3200/3000/2933/2666/2400/2133 MHz memory modules | 2 x DDR4 DIMM sockets supporting up to 64 GB (32 GB single DIMM capacity) of system memory |
| Dual channel memory architecture | Support for ECC Un-buffered DIMM 1Rx8/2Rx8 memory modules (operate in non-ECC mode) |
| Support for non-ECC Un-buffered DIMM 1Rx8/2Rx8/1Rx16 memory modules | Support for Extreme Memory Profile (XMP) memory modules |

(Please refer "Memory Support List" for more information.)

Onboard Graphics

Integrated Graphics Processor-Intel® HD Graphics support:

| | |
|---|---|
| 1 x D-Sub port, supporting a maximum resolution of 1920x1200@60 Hz | 1 x DVI-D port, supporting a maximum resolution of 1920x1200@60 Hz<br>* The DVI-D port does not support D-Sub connection by adapter. |
| 1 x HDMI port, supporting a maximum resolution of 4096x2160@60 Hz<br>* Support for HDMI 2.1 version and HDCP 2.3.<br>** Support native HDMI 2.1 TMDS compatible ports | 1 x DisplayPort, supporting a maximum resolution of 4096x2304@60 Hz<br>* Support for DisplayPort 1.2 version and HDCP 2.3 |

(Graphics specifications may vary depending on CPU support.)

Audio

| | |
|---|---|
| Realtek® Audio CODEC | High Definition Audio |
| 2/4/5.1/7.1-channel<br>* To configure 7.1-channel audio, you need to open the audio software and select Device advanced settings > Playback Device to change the default setting first. Please visit GIGABYTE's website for details on configuring the audio software. | |

Expansion Slots

| | |
|---|---|
| 1 x PCI Express x16 slot, running at x16<br>* For optimum performance, if only one PCI Express graphics card is to be installed, be sure to install it in the PCIEX16 slot. (The PCI Express x16 slot conforms to PCI Express 4.0 standard.) | 1 x PCI Express x1 slot (The PCI Express x1 slot conforms to PCI Express 3.0 standard.) |

USB

Chipset:

| | |
|---|---|
| 4 x USB 3.2 Gen 1 ports (2 ports on the back panel, 2 ports available through the internal USB header) | 4 x USB 2.0/1.1 ports on the back panel |

Chipset+USB 2.0 Hub:

| | |
|---|---|
| 4 x USB 2.0/1.1 ports available through the internal USB headers | |

Back Panel Connectors

| | |
|---|---|
| 1 x PS/2 keyboard port | 1 x PS/2 mouse port |
| 1 x D-Sub port | 1 x DVI-D port |
| 1 x DisplayPort | 1 x HDMI 2.0 port |
| 2 x USB 3.2 Gen 1 ports | 4 x USB 2.0/1.1 ports |
| 1 x RJ-45 port | 3 x audio jacks |

H/W Monitoring

| | |
|---|---|
| Voltage detection | Temperature detection |
| Fan speed detection | Overheating warning |
| Fan fail warning | Fan speed control<br>* Whether the fan speed control function is supported will depend on the cooler you install. |

LAN

| |
|---|
| Intel® GbE LAN chip (1 Gbps/100 Mbps) |

Storage Interface

Chipset:

| | |
|---|---|
| 1 x M.2 connector (Socket 3, M key, type 2260/2280 PCIe 3.0 x4/x2 SSD support) | 4 x SATA 6Gb/s connectors |

Internal I/O Connectors

| | |
|---|---|
| 1 x 24-pin ATX main power connector | 1 x 8-pin ATX 12V power connector |
| 1 x M.2 Socket 3 connector | 4 x SATA 6Gb/s connectors |
| 1 x CPU fan header | 2 x system fan headers |
| 1 x RGB LED strip header | 1 x front panel header |
| 1 x front panel audio header | 1 x USB 3.2 Gen 1 header |
| 2 x USB 2.0/1.1 headers | 1 x Trusted Platform Module header (For the GC-TPM2.0 SPI/GC-TPM2.0 SPI 2.0 module only) |
| 1 x serial port header | 1 x Clear CMOS jumper |

I/O Controller

| |
|---|
| iTE® I/O Controller Chip |

BIOS

| | |
|---|---|
| 1 x 256 Mbit flash | Use of licensed AMI UEFI BIOS |
| PnP 1.0a, DMI 2.7, WfM 2.0, SM BIOS 2.7, ACPI 5.0 | |

Unique Features

- Support for APP Center
  * Available applications in APP Center may vary by motherboard model. Supported functions of each application may also vary depending on motherboard specifications.
- @BIOS
- Ambient LED
- EasyTune
- Fast Boot
- Game Boost
- ON/OFF Charge
- Smart Backup
- System Information Viewer
- Support for Q-Flash
- Support for Xpress Install

Bundled Software

- Norton® Internet Security (OEM version)
- LAN bandwidth management software

Operating System

Form Factor

Cene su informativnog karaktera. Prodavac ne odgovara za tačnost cena iskazanih na sajtu, zadržava pravo izmena cena. Ponudu za ostale artikle, informacije o stanju lagera i aktuelnim cenama možete dobiti na upit. Plaćanje se isključivo vrši virmanski - bezgotovinski.