

Tenda O6 outdoor long range Point to Point CPE 5GHz 11AC 433Mbps, 16dB, 10km

Šifra: 34824
Kategorija proizvoda: Mrežna oprema
Proizvođač: TENDA

Cena: 11.420,00



Dimension 270*94.86*67.5mm
Frequency Range 5GHz
Maximum wireless speed 433Mbps
CPU Processor Broadcom 800MHz
GND Terminal 1
Interface 1*GE PoE/WAN/LAN port
Mode Switch Station: The device only work in Station mode
Off: The device work on
AP/Station/Universal Repeater/WISP/Router mode
AP: The device only work in AP mode
Button Reset: Press 10 seconds or more to restore to default settings
Bridge: Press 3 seconds and release it to bridge uplink AP
Antenna 16dbi Directional Antenna
Antenna Beamwidth Horizontal: 30°
Vertical: 15°
Maximum Consumption 9W
Lightning Protection 6KV
Waterproof Level IP64
LED LAN, LED1, LED2, LED3
Power Supply 24v 0.5A PoE Injector
Operating mode AP/Station/Universal Repeater/WISP/Router
Standard & Protocol IEEE 802.11ac/n/a
Wireless Speed Enable/Disable Wireless Radio
SSID Hidden
Wireless Client isolation
Sensitivity Threshold
WMM Capable
APSD Capable
Wireless Access Control
Wireless Client list
Wireless Security 64/128 WEP, WPA-PSK, WPA2-PSK, WPA&WPA2-PSK, WPA, WPA2
Transmit Power Adjustable power by 1dBm
Reception Sensitivity MCS0: -90dbm
MCS7: -72dbm
DHCP Server DHCP Server
Clients list
VPN Pass-through PPTP, L2TP
Ping Watchdog Support
Speed Test Support
Remote Web access Support
Schedule Reboot Support
Page Timeout Support

Dyndnsnoip, dyndns.org
Network DiagnosesPing, Traceroute, Signal Scan
Management ToolTime&Date Setting
System Log
Firmware update
Backup/Restore Configuration
Username Managerment
TemperatureOperating Temperature:-20? ~ 55?
Storage Temperature:-40? ~ 70?
HumidityOperating Humidity:10%~90% non-condensing
Storage Humidity:10%~90% non-condensing
Default SettingsIP Address: 192.168.2.1
Login Username:admin
Login Password:admin
CertificationFCC/CE/RoHS