

logo not found or type unknown

Firma: PC COOL DOO  
Adresa: Višegradaska 26A  
Telefon: 0653526116  
Fax:  
PIB: 104045201  
E-mail: info@pccool.rs

Ruter TP-LINK Archer C24 AC750 dual band  
733Mbps

Šifra: 35800  
Kategorija proizvoda: Mrežna oprema  
Proizvođač: TP-Link

Cena: 3.320,00



| WIRELESS          |                                                                                                                                         |
|-------------------|-----------------------------------------------------------------------------------------------------------------------------------------|
| Standards         | <b>Wi-Fi 5</b><br>IEEE 802.11ac/n/a 5 GHz<br>IEEE 802.11n/b/g 2.4 GHz                                                                   |
| WiFi Speeds       | <b>AC750</b><br>5 GHz: 433 Mbps (802.11ac)<br>2.4 GHz: 300 Mbps (802.11n)                                                               |
| WiFi Range        | <b>2 Bedroom Houses</b><br>4× Fixed Antennas<br>Multiple antennas form a signal-boosting array to cover more directions and large areas |
| WiFi Capacity     | <b>Medium</b><br>Dual-Band<br>Allocate devices to different bands for optimal performance                                               |
| Working Modes     | Router Mode<br>Access Point Mode<br>Range Extender Mode                                                                                 |
| HARDWARE          |                                                                                                                                         |
| Processor         | Single-Core CPU                                                                                                                         |
| Ethernet Ports    | 1× 10/100 Mbps WAN Port<br>4× 10/100 Mbps LAN Ports                                                                                     |
| Buttons           | WPS/Reset Button                                                                                                                        |
| Power             | 9 V ? 0.6 A                                                                                                                             |
| SECURITY          |                                                                                                                                         |
| WiFi Encryption   | WEP<br>WPA<br>WPA2<br>WPA/WPA2-Enterprise (802.1x)                                                                                      |
| Network Security  | SPI Firewall<br>Access Control<br>IP & MAC Binding<br>Application Layer Gateway                                                         |
| Guest Network     | 1× 5 GHz Guest Network<br>1× 2.4 GHz Guest Network                                                                                      |
| SOFTWARE          |                                                                                                                                         |
| Protocols         | IPv4<br>IPv6                                                                                                                            |
| Parental Controls | URL Filtering<br>Time Controls                                                                                                          |

| SOFTWARE                   |                                                                                                                                                                                                                        |
|----------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| WAN Types                  | Dynamic IP<br>Static IP<br>PPPoE<br>PPTP<br>L2TP                                                                                                                                                                       |
| Quality of Service         | QoS by Device                                                                                                                                                                                                          |
| NAT Forwarding             | Port Forwarding<br>Port Triggering<br>DMZ<br>UPnP                                                                                                                                                                      |
| IPTV                       | IGMP Proxy<br>IGMP Snooping<br>Bridge<br>Tag VLAN                                                                                                                                                                      |
| DHCP                       | Address Reservation<br>DHCP Client List<br>Server                                                                                                                                                                      |
| DDNS                       | NO-IP<br>DynDNS                                                                                                                                                                                                        |
| Management                 | Tether App<br>Webpage<br><a href="#">Check Web Emulator&gt;</a>                                                                                                                                                        |
| PHYSICAL                   |                                                                                                                                                                                                                        |
| Dimensions (W×D×H)         | 4.5 × 4.2 × 1.0 in<br>(115 × 106.7 × 24.3 mm)                                                                                                                                                                          |
| Package Contents           | Wi-Fi Router Archer C24<br>Power Adapter<br>RJ45 Ethernet Cable<br>Quick Installation Guide                                                                                                                            |
| OTHER                      |                                                                                                                                                                                                                        |
| System Requirements        | Internet Explorer 11+, Firefox 12.0+, Chrome 20.0+, Safari 4.0+, or other JavaScript-enabled browser<br><br>Cable or DSL Modem (if needed)<br><br>Subscription with an internet service provider (for internet access) |
| Certifications             | FCC, CE, RoHS                                                                                                                                                                                                          |
| Environment                | Operating Temperature: 0?~40? (32? ~104?)<br>Storage Temperature: -40?~60? (-40? ~140?)<br>Operating Humidity: 10%~90% non-condensing<br>Storage Humidity: 5%~90% non-condensing                                       |
| TEST DATA                  |                                                                                                                                                                                                                        |
| WiFi Transmission Power    | CE:<br><20dBm(2.4GHz)<br><23dBm(5GHz)                                                                                                                                                                                  |
| WiFi Reception Sensitivity | 5GHz:<br>11a 54M: -76dBm;<br>11ac VHT20 MCS8: -71dBm;<br>11ac VHT40 MCS9: -66dBm;<br>11ac VHT80 MCS9: -62dBm<br>2.4GHz:<br>11g 54M: -76dBm;<br>11n HT20 MCS7: -73dBm;<br>11n HT40 MCS7: -71dBm                         |