

Kamera dahua IPC-HFW2439S-SA-LED-0360B
4Mpix, 3.6 mm, IP kamera, metalno kuciste

Šifra: 38634
Kategorija proizvoda: HDCVI kamere, HDCVI snimači
Proizvođač: DAHUA

Cena: **10.830,00**



IP 4MP bullet Full Color kamera;

Lite serija;

Bele LE diode 30m;

3.6mm; IP67;

Micro SD slot.

IP bullet Full Color kamera 4MP. 1/3" CMOS, progresivno skeniranje (2688×1520 piksela).

Starlight. Osetljivost 0.004Lux /F1.0 (kolor), 0Lux (beli LED aktivan.).

Bele LE diode dometa cca. 30m

Objektiv 3.6mm F1.0 Horizontal 81° × Vertical 44° × Diagonal 97°. BLC/ HLC/ WDR 120dB. 3D DNR. ROI.

Masking (do 4 zone). H.265 /H.264 /H.265B /MJPEG kompresija.

Smart codec podrška.

Rezolucije 2688×1520 /2048×1536 /2304 × 1296 /1080P /1.3M /720P /D1 /VGA /CIF. Dual Stream. Do

20fps u 2688×1520, do 25/30fps u 2560 × 1440 i nižim rezolucijama. RJ-45 (10/100Base-T) mrežni port.

Protokoli IPv4, IPv6, HTTP, HTTPS, TCP, UDP, ARP, RTP, RTSP, RTCP, RTMP, SMTP, FTP, SFTP, DHCP, DNS,

DDNS, QoS, UPnP, NTP, Multicast, ICMP, IGMP, NFS, PPPoE, 802.1x, Bonjour. Interoperabilnost: ONVIF

(Profile S/Profile G), CGI, P2P, Milestone, Genetec. Micro SD slot (do. 256GB).

Video analitika - detekcija prelaska definisane linije i ulaska/izlaska u definisani region. Potrebno napajanje 12VDC ili PoE (802.3af).

Potrošnja 6.2W.

Dimenzije 100.9mm × F109.9mm.

Masa 0.365kg.

IP67. Radna temp. -40°C~+60°C. CE-LVD: EN62368-1, CE-EMC: Electromagnetic Compatibility Directive 2014/30/EU.