

MB AMD AM4 Gigabyte A520M K V2

Šifra: 40165

Kategorija proizvoda: Matične ploče

Proizvođač: GIGABYTE

Cena: **6.290,00**



Model	Gigabyte A520M K V2 Matična ploča DDR4 AM4 Micro ATX
Procesorsko podnožje (Socket)	AMD Socket AM4
Skup čipova (Chipset)	AMD A520
Podrška za procesore	AMD Socket AM4, support for: AMD Ryzen™ 5000 G-Series Processors/ AMD Ryzen™ 5000 Series Processors/ AMD Ryzen™ 4000 G-Series Processors/ AMD Ryzen™ 3000 Series Processors
Tip memorije (RAM)	DDR4
Broj memorijskih slotova	2x 288-Pin DDR4
Podrška za memorije	2 x DDR4 DIMM sockets supporting up to 64 GB (32 GB single DIMM capacity) of system memory Support for DDR4 5100(O.C.) / 4800(O.C.) / 4600(O.C.) / 4400(O.C.) / 4266(O.C.) / 4133(O.C.) / 4000(O.C.) / 3866(O.C.) / 3733(O.C.) / 3600(O.C.) / 3466(O.C.) / 3400(O.C.) / 3200 / 2933 / 2667 / 2400 / 2133 MHz memory modules Dual channel memory architecture Support for ECC Un-buffered DIMM 1Rx8/2Rx8 memory modules (operate in non-ECC mode) Support for non-ECC Un-buffered DIMM 1Rx8/2Rx8/1Rx16 memory modules Support for Extreme Memory Profile (XMP) memory modules
Podrška za grafiku - portovi	Integrated Graphics Processor: 1 x D-Sub port, supporting a maximum resolution of 1920x1200@60 Hz 1 x HDMI port, supporting a maximum resolution of 4096x2160@60 Hz Maximum shared memory of 16 GB
Slotovi za proširenja	CPU: 1 x PCI Express x16 slot, supporting PCIe 3.0 and running at x16 Chipset: 1 x PCI Express x1 slot, supporting PCIe 3.0 and running at x1
M.2 portovi	1x M.2 Socket 3
Čuvanje podataka - portovi	CPU: 1 x M.2 connector (Socket 3, M key, type 2280 SATA and PCIe 3.0 x4/x2 SSD support) Chipset: 4 x SATA 6Gb/s connectors Support for RAID 0, RAID 1, and RAID 10
U.2 portovi	nema
SATA Express portovi	nema

SATA portovi	4x SATA 6Gb/s
LAN	Realtek® GbE LAN chip (1 Gbps/100 Mbps)
Zvuk (Audio)	Realtek® Audio CODEC High Definition Audio 2/4/5.1/7.1-channel
USB portovi	CPU: 4 x USB 3.2 Gen 1 ports on the back panel Chipset: 2 x USB 3.2 Gen 1 ports available through the internal USB header 6 x USB 2.0/1.1 ports (2 ports on the back panel, 4 ports available through the internal USB headers)
Konektori na zadnjoj strani	1 x PS/2 keyboard/mouse port 1 x D-Sub port 1 x HDMI port 4 x USB 3.2 Gen 1 ports 2 x USB 2.0/1.1 ports 1 x RJ-45 port 3 x audio jacks
Unutrašnji konektori	1 x 24-pin ATX main power connector 1 x 8-pin ATX 12V power connector 1 x CPU fan header 1 x system fan header 1 x M.2 Socket 3 connector 4 x SATA 6Gb/s connectors 1 x front panel header 1 x front panel audio header 1 x USB 3.2 Gen 1 header 2 x USB 2.0/1.1 headers 1 x Trusted Platform Module (TPM) header (2x6 pin, for the GC-TPM2.0_S module only) 1 x speaker header 1 x Clear CMOS jumper 1 x chassis intrusion header
Posebne mogućnosti	Support for APP Center @BIOS EasyTune Smart Backup System Information Viewer Support for Q-Flash Support for Xpress Install
Operativni sistem	Windows® 10; Windows® 11
BIOS	1 x 128 Mbit flash Use of licensed AMI UEFI BIOS PnP 1.0a, DMI 2.7, WfM 2.0, SM BIOS 2.7, ACPI 5.0
Format	Micro ATX