Firma: PC COOL DOO
Adresa: Višegradska 26A
Telefon: 0653526116
Fax:
PIB: 104045201
E-mail: info@pccool.rs

MB Gigabyte AMD AM4 A520M DS3H V2 1.0

Šifra: 43506
Kategorija prozivoda: Matične ploče
Proizvođač: GIGABYTE

Cena: 7.590,00



CPU
AMD Socket AM4, support for: AMD Ryzen™ 5000 Series/ Ryzen™ 5000 G-Series/ Ryzen™ 4000 G-Series and Ryzen™ 3000 Series Processors
(Please refer "CPU Support List" for more information.)

Chipset
AMD A520

Memory

4 x DDR4 DIMM sockets supporting up to 128 GB (32 GB single DIMM capacity) of system memory	Support for DDR4 4733(O.C.) / 4600(O.C.) / 4400(O.C.) / 4266(O.C.) / 4133(O.C.) / 4000(O.C.) / 3866(O.C.) / 3733(O.C.) / 3600(O.C.) / 3466(O.C) / 3400(O.C.) / 3200 / 2933 / 2667 / 2400 / 2133 MHz memory modules
Dual channel memory architecture	Support for ECC Un-buffered DIMM 1Rx8/2Rx8 memory modules
Support for non-ECC Un-buffered DIMM 1Rx8/2Rx8/1Rx16 memory modules	Support for Extreme Memory Profile (XMP) memory modules

(Please refer "Memory Support List" for more information.)

Onboard Graphics
Integrated Graphics Processor:

1 x DisplayPort, supporting a maximum resolution of 5120x2880@60 Hz * Support for DisplayPort 1.4 version, HDCP 2.3, and HDR.	1 x HDMI port, supporting a maximum resolution of 4096x2160@60 Hz * Support for HDMI 2.1 version, HDCP 2.3, and HDR.

Maximum shared memory of 16 GB

Audio

Realtek® Audio CODEC	High Definition Audio
2/4/5.1/7.1-channel * You can change the functionality of an audio jack using the audio software. To configure 7.1-channel audio, access the audio software for audio settings.	

LAN
Realtek® GbE LAN chip (1 Gbps/100 Mbps)

Expansion Slots
1 x PCI Express x16 slot, integrated in the CPU:
- Supporting PCIe 3.0 x16 mode

1 x PCI Express x1 slot, integrated in the Chipset:
- Supporting PCIe 3.0 x1 mode

USB
CPU:
- 4 x USB 3.2 Gen 1 ports on the back panel

Chipset:
- 2 x USB 3.2 Gen 1 ports available through the internal USB header
- 6 x USB 2.0/1.1 ports (4 ports on the back panel, 2 ports available through the internal USB header)

Back Panel Connectors
- 1 x PS/2 keyboard/mouse port
- 1 x HDMI port
- 2 x USB 2.0/1.1 ports
- 3 x audio jacks
- 1 x DisplayPort
- 4 x USB 3.2 Gen 1 ports
- 1 x RJ-45 port

H/W Monitoring
- Voltage detection
- Temperature detection
- Fan speed detection
- Fan fail warning
- Fan speed control
  * Whether the fan speed control function is supported will depend on the cooler you install.

Unique Features
- Support for APP Center
  * Available applications in APP Center may vary by motherboard model. Supported functions of each application may also vary depending on motherboard specifications.
- @BIOS
- EasyTune
- Smart Backup
- System Information Viewer
- Support for Q-Flash
- Support for Xpress Install

Operating System
- Support for

Storage Interface
1 x M.2 connector, integrated in the CPU, supporting Socket 3, M key, type 2280 SSDs:
- Supporting SATA and PCIe 3.0 x4/x2 SSDs

4 x SATA 6Gb/s connectors, integrated in the Chipset:
- Supporting for RAID 0, RAID 1, and RAID 10

Internal I/O Connectors
- 1 x 24-pin ATX main power connector
- 1 x 8-pin ATX 12V power connector
- 1 x CPU fan header
- 1 x system fan header
- 1 x M.2 Socket 3 connector
- 4 x SATA 6Gb/s connectors
- 1 x front panel header
- 1 x front panel audio header
- 1 x USB 3.2 Gen 1 header
- 1 x USB 2.0/1.1 header
- 1 x Trusted Platform Module (TPM) header (2x6 pin, for the GC-TPM2.0_S module only)
- 1 x Clear CMOS jumper

I/O Controller
- iTE® I/O Controller Chip

BIOS
- 1 x 128 Mbit flash
- Use of licensed AMI UEFI BIOS
- PnP 1.0a, DMI 2.7, WfM 2.0, SM BIOS 2.7, ACPI 5.0

Bundled Software
- Norton® Internet Security (OEM version)
- LAN bandwidth management software

Form Factor
- Micro ATX Form

Cene su informativnog karaktera. Prodavac ne odgovara za tačnost cena iskazanih na sajtu, zadržava pravo izmena cena. Ponudu za ostale artikle, informacije o stanju lagera i aktuelnim cenama možete dobiti na upit. Plaćanje se isključivo vrši virmanski - bezgotovinski.