Firma: PC COOL DOO
Adresa: Višegradska 26A
Telefon: 0653526116
Fax:
PIB: 104045201
E-mail: info@pccool.rs

Matična ploča AM4 Gigabyte A520 AORUS ELITE DVIHDMIM.2

Šifra: 49489
Kategorija prozivoda: Matične ploče
Proizvođač: GIGABYTE

Cena: 9.950,00



Tip procesora:	AMD
Podnožje:	AMD® AM4
Čipset:	AMD® A520
Format ploče:	ATX
Podržana memorija:	DDR4
Podržani procesori:	AMD podnožje AM4, podržava AMD Ryzen 5000 Series / 3rd Generation AMD Ryzen procesora / 3rd Generation AMD Ryzen sa Radeon grafičkim procesorima
Memorija:	- 4 x DDR4 DIMM podnožja podržavaju do 128 GB (32 GB single DIMM capacity) sistemske memorije - AMD Ryzen 5000 serije procesora: - Podržava DDR4 4266(O.C.) / 4000(O.C.) / 3866(O.C.) / 3800(O.C.) / 3733(O.C.) / 3600(O.C.) / 3466(O.C.) / 3400(O.C.) / 3333(O.C.) / 3300(O.C.) / 3200 / 2933 / 2667 / 2400 / 2133 MHz memorijske module - 3rd Gen AMD Ryzen Procesore: - Podržava DDR4 4400(O.C.) / 4000(O.C.) / 3600(O.C.) / 3333(O.C.) / 3200 / 2933 / 2667 / 2400 / 2133 MHz memorijske module - 3rd Gen AMD Ryzen sa Radeon grafičkim procesorima: - Podržava DDR4 4733(O.C.) / 4600(O.C.) / 4400(O.C.) / 4000(O.C.) / 3600(O.C.) / 3333(O.C.) / 3200 / 2933 / 2667 / 2400 / 2133 MHz memorijske module

	- Dual channel memory architecture - Podržava ECC Un-buffered DIMM 1Rx8/2Rx8 memorijske module - Podržava non-ECC Un-buffered DIMM 1Rx8/2Rx8/1Rx16 memorijske module - Podržava Extreme Memory Profile (XMP) memorijske module
Integrisana grafička karta:	Integrisana u trećoj generaciji AMD Ryzen sa Radeon grafičkim procesorima: - 1 x DVI-D port, podržava maksimalnu rezoluciju od 1920x1200 @60 Hz - DVI-D port ne podržava D-Sub konekciju putem adaptera. - 1 x HDMI port, podržava maksimalnu rezoluciju od 4096x2160 @60 Hz - Podržava HDMI 2.1 verziju, HDCP 2.3, i HDR. - Maksimalna deljena memorija 16 GB
Slotovi za proširenje:	CPU: - 1 x PCI Express x16 slot, podržava PCIe 3.0 i radi na x16 (PCIEX16) Chipset: - 1 x PCI Express x16 slot, podržava PCIe 3.0 i radi na x2 (PCIEX2) - 3 x PCI Express x1 slots, podržava PCIe 3.0 (PCIEX1_1, PCIEX1_2, PCIEX1_3)
Skladište:	CPU: - 1 x M.2 konektor (podnožje 3, M key, tip 2242/2260/2280/22110 SATA i PCIe 3.0 x4/x2 SSD podrška) Chipset: - 4 x SATA 6Gb/s konektora - Podržava RAID 0, RAID 1, i RAID 10
Mrežna karta:	- Realtek GbE LAN chip (1000 Mbit/100 Mbit)
Zvučna karta:	- Realtek ALC1200 codec - High Definition Audio - 2/4/5.1/7.1-channel - Podržava S/PDIF Out
USB:	CPU: - 1 x USB 3.2 Gen 2 Type-A port (crveni) na zadnjem panelu - 3 x USB 3.2 Gen 1 porta na zadnjem panelu Chipset: - 2 x USB 3.2 Gen 1 porta dostupni putem internih USB header - 4 x USB 2.0/1.1 porta dostupni putem internih USB headers Chipset+USB 2.0 Hub: - 4 x USB 2.0/1.1 porta na zadnjem panelu
Konektori na zadnjoj strani:	- 1 x PS/2 keyboard/mouse port - 1 x DVI-D port - 1 x HDMI port - 1 x USB 3.2 Gen 2 Type-A port (red) - 3 x USB 3.2 Gen 1 ports - 4 x USB 2.0/1.1 ports - 1 x RJ-45 port - 1 x optical S/PDIF Out connector - 5 x audio jacks
Interni konektori:	- 1 x 24-pin ATX main power connector - 1 x 8-pin ATX 12V power connector - 1 x CPU fan header - 1 x water cooling CPU fan header - 3 x system fan headers - 2 x addressable LED strip headers - 2 x RGB LED strip headers - 1 x M.2 Socket 3 connector - 4 x SATA 6Gb/s connectors - 1 x front panel header - 1 x front panel audio header - 1 x USB 3.2 Gen 1 header - 2 x USB 2.0/1.1 headers - 1 x Trusted Platform Module (TPM) header (2x6 pin, for the GC-TPM2.0_S module only) - 1 x serial port header - 1 x Clear CMOS jumper - 1 x Q-Flash Plus button
BIOS:	- 1 x 128 Mbit flash - Use of licensed AMI UEFI BIOS - PnP 1.0a, DMI 2.7, WfM 2.0, SM BIOS 2.7, ACPI 5.0
Proizvođačka	Zakonska garancija 2 godine

Cene su informativnog karaktera. Prodavac ne odgovara za tačnost cena iskazanih na sajtu, zadržava pravo izmena cena. Ponudu za ostale artikle, informacije o stanju lagera i aktuelnim cenama možete dobiti na upit. Plaćanje se isključivo vrši virmanski - bezgotovinski.