Firma: PC COOL DOO
Adresa: Višegradska 26A
Telefon: 0653526116
Fax:
PIB: 104045201
E-mail: info@pccool.rs

TP-Link EAP225 - Outdoor IP65

Šifra: 71648
Kategorija prozivoda: Access Point
Proizvođač: TP-Link

Cena: 15.480,00



Interfejs	• 1× Gigabit Ethernet (RJ-45) Port (Podrška za 802.3af/at PoE (Alternativa A) i pasivni PoE) • Dugme Reset

Napajanje	• 802.3af/at PoE (Alternativa A) • 24V pasivni PoE (+4,5pins; -7,8pins. Uključen PoE adapter) • Potrošnja energije: 10.5 W
Antena	• 2.4 GHz: 2× 3 dBi • 5 GHz: 2× 4 dBi
Zaštita od vremenskih uslova	IP65
Montaža	Pole/Wall Mounting (Kits included)
Bežične funkcije	• Concurrent Clients: 220+** • Wireless Standards: IEEE 802.11a/b/g/n/ac • Frekvencija: 2.4GHz, 5GHz • Signal Rate: -802.11ac: 5G: 6.5 Mbps do 867 Mbps, 2.4G: 78 Mbps do 300 Mbps -802.11n: 6.5 Mbps do 300 Mbps -802.11g: 6, 9, 12, 18, 24, 36, 48, 54 Mbps -802.11b: 1, 5.5, 11 Mbps -802.11a: 6, 9, 12, 18, 24, 36, 48, 54 Mbps • Wireless Functions: -Multiple SSIDs (do 16 SSID-ova, 8 po opsegu) -Enable/Disable Wireless Radio -Automatic Channel Assignment -Transmit Power Control (Podešavanje snage transmitovanja u dBm) -QoS (WMM) -MU-MIMO -Seamless Roaming -Omada Mesh -Airtime Fairness -Beamforming -Band Steering -Load Balance -Rate Limit -Reboot Schedule -Wireless Schedule -Wireless Statistics based on SSID/AP/Client
Bežična sigurnost	• Captive Portal Authentication • Access Control • Wireless Mac Address Filtering • Wireless Isolation Between Clients • SSID to VLAN Mapping • Rogue AP Detection • 802.1X Support
Snaga prenosa	• CE: <20 dBm (2.4 GHz), <27 dBm (5 GHz) • FCC: <23 dBm (2.4 GHz), <22 dBm (5 GHz)
Upravljanje	• Omada App: Da • Centralized Management: -Omada Cloud-Based Controller -Omada Hardware Controller (OC300) -Omada Hardware Controller (OC200) -Omada Software Controller • Cloud Access: Da (zahteva OC300, OC200, Omada Cloud-Based Controller ili Omada Software Controller) • Email Alerts: Da • Management MAC Access Control: Da • SNMP: v1, v2c • System Logging Local/Remote Syslog: Da • SSH: Da • Web-based Management: Da • L3 Management: Da • Multi-site Management: Da • Management VLAN: Da • Zero-Touch Provisioning: Da (zahteva Omada Cloud-Based Controller)
Ostalo	• Certification: CE, FCC, RoHS • Package Contents: -Access Point EAP225-Outdoor -Passive PoE Adapter -Power Cord -Mounting Kits -Installation Guide -Waterproof Rubber Insert

	-Waterproof Antenna • System Requirements: Microsoft Windows XP, Vista, Windows 7, Windows 8, Windows 10, Windows 11, Linux
Okruženje	• Operating Temperature: -30–70 ? (-22–158 ?) • Storage Temperature: -40–70 ? (-40–158 ?) • Operating Humidity: 10–90% RH non-condensing • Storage Humidity: 5–90% RH non-condensing
Dimenzije	Dimenzije (Š x D x V): 46 × 26.7 × 214.9 mm (1.8 × 1.1 × 8.5 in) (bez antene i kompleta za montažu)
Prava	

Cene su informativnog karaktera. Prodavac ne odgovara za tačnost cena iskazanih na sajtu, zadržava pravo izmena cena. Ponudu za ostale artikle, informacije o stanju lagera i aktuelnim cenama možete dobiti na upit. Plaćanje se isključivo vrši virmanski - bezgotovinski.