

## LAN Router TP-LINK TL-MR6400 3G4G LTE

Šifra: 87518  
 Kategorija proizvoda: Mrežna oprema  
 Proizvođač: TP-Link

Cena: **9.240,00**



<b>HARDWARE FEATURES</b>	
<b>Ports</b>	3× 10/100 Mbps LAN ports, 1× 10/100 Mbps LAN/WAN Port, 1× Nano SIM Card Slot
<b>Button</b>	WPS/RESET Button, WiFi ON/OFF Button
<b>External Power Supply(EU)</b>	9V/0.85A
<b>Dimensions ( W x D x H )</b>	6.85 × 4.9 × 1.32 in. (174 × 124.5 × 33.5 mm)
<b>Antenna Type</b>	2× Detachable External 4G LTE Antennas
<b>WIRELESS FEATURES</b>	
<b>Wireless Standards</b>	IEEE 802.11b, 802.11g, 802.11n
<b>Frequency</b>	2.4 GHz
<b>Signal Rate</b>	300 Mbps at 2.4 GHz
<b>Reception Sensitivity</b>	11g 54M: -74 dBm 11n HT20: -71 dBm 11n HT40: -67 dBm
<b>Transmit Power</b>	<20 dBm (2.4 GHz)
<b>Wireless Functions</b>	Enable/Disable Wireless Radio, Wireless Schedule, WMM, Wireless Statistics
<b>WAN Failover</b>	Yes
<b>Wireless Security</b>	64/128-bit WEP, WPA/WPA2, WPA-PSK/WPA2-PSK encryptions
<b>Network Type</b>	4G: FDD-LTE Cat4 (800/900/1800/2100/2600 MHz), TDD-LTE (2300/2500/2600 MHz) 3G: DC-HSPA+/HSPA+/HSPA/UMTS (900/2100 MHz)
<b>SOFTWARE FEATURES</b>	
<b>Quality of Service</b>	WMM, QoS
<b>Operating Modes</b>	3G/4G Router, Wireless Router
<b>Management</b>	Access Control, Local Management, Remote Management
<b>WAN Connection Type</b>	Dynamic IP/Static IP/PPPoE/PPTP(Dual Access)/L2TP(Dual Access)
<b>DHCP</b>	Server, Client, DHCP Client List, Address Reservation
<b>Port Forwarding</b>	Virtual Server, Port Triggering, UPnP, DMZ
<b>Dynamic DNS</b>	TP-Link DDNS, DynDns, NO-IP
<b>VPN Pass-Through</b>	PPTP, L2TP, IPSec
<b>Access Control</b>	Parental Controls, Local Management Control, Host List, Access Control
<b>Firewall Security</b>	DoS, SPI Firewall, IP and MAC Address Binding
<b>Protocols</b>	Supports IPv4 and IPv6
<b>Guest Network</b>	2.4 GHz Guest Network
<b>VPN Server</b>	PPTP VPN, OpenVPN
<b>OTHERS</b>	
<b>Certification</b>	CE, RoHS

**OTHERS**

<b>Package Contents</b>	300Mbps Wireless N 4G LTE Router TL-MR6400 Power Adapter RJ45 Ethernet Cable Quick Installation Guide
<b>System Requirements</b>	Microsoft Windows 98SE, NT, 2000, XP, Vista™ or Windows 7, 8, 8.1, MAC OS, NetWare, UNIX or Linux Internet Explorer 11, Firefox 12.0, Chrome 20.0, Safari 4.0 browser or higher, or other Java-enabled browsers Nano SIM Card
<b>Environment</b>	Operating Temperature: 0?~40? (32? ~104?) Storage Temperature: -40?~60? (-40? ~140?) Operating Humidity: 10%~90% non-condensing Storage Humidity: 5%~90% non-condensing