

MB AM5 GIGABYTE A620M GAMING X rev. 1.0

Šifra: 93386
Kategorija proizvoda: Matične ploče
Proizvođač: GIGABYTE

Cena: **13.170,00**



CPU

AMD Socket AM5,
support for: AMD
Ryzen™ 7000 / Ryzen™
8000 / Ryzen™ 9000
Series Processors
(Please refer "CPU Support List" for more information.)

Chipset

AMD A620

Memor

Supp
8000
7600
7000
6600
6200
5600
Audio
MT/s

Onboard Graphics

Integrated Graphics Processor:

1 x DisplayPort,
supporting a maximum
resolution of
3840x2160@144 Hz
* Support for DisplayPort
1.4 version.

1 x HDMI port,
supporting a maximum
resolution of
4096x2160@60 Hz
* Support for HDMI 2.1
version and HDCP 2.3.
** Support native HDMI
2.1 TMDS compatible
ports.

(Graphics specifications may vary depending on CPU
support.)

(The CI
support
numbe
Support

Realtek® Audio CODEC	High Definition Audio 2/4/5.1/7.1-channel * You can change the functionality of an audio jack using the audio software. To configure 7.1-channel audio, access the audio software for audio settings.	LAN Realtek® GbE LAN chip (1 Gbps/100 Mbps)	Expansion 1 x PCI CPU: AMD Series supp mode
		Storage Interface 1 x M.2 connector, integrated in the CPU, supporting Socket 3, M key, type 2580/2280 SSDs: AMD Ryzen™ 7000 Series Processors support PCIe 4.0 x4/x2 SSDs AMD Ryzen™ 8000 Series-Phoenix 1 Processors support PCIe 4.0 x4/x2 SSDs AMD Ryzen™ 8000 Series-Phoenix 2 Processors support PCIe 4.0 x4/x2 SSDs	USB CPU: 1 x U A por panel
		4 x SATA 6Gb/s connectors RAID 0, RAID 1, and RAID 10 support for NVMe SSD storage devices RAID 0, RAID 1, and RAID 10 support for SATA storage devices	Chipse 1 x p suppl suppl throu head
		Internal I/O Connectors 1 x 24-pin ATX main power connector 1 x 8-pin ATX 12V power connector 1 x CPU fan header 2 x system fan headers 1 x addressable LED strip header 1 x RGB LED strip header 1 x M.2 Socket 3 connector 4 x SATA 6Gb/s connectors 1 x front panel header 1 x front panel audio header 1 x USB Type-C® header, with USB 3.2 Gen 1 support 1 x USB 3.2 Gen 1 header 1 x USB 2.0/1.1 header 1 x Trusted Platform Module header (For the GC-TPM2.0 SPI/GC-TPM2.0 SPI 2.0 module)	

only)	1 x Clear CMOS jumper	Back Panel Connectors 1 x PS/2 keyboard/mouse port	1 x USB Type-C® port, with USB 3.2 Gen 1 support 1 x USB 3.2 Gen 2 Type- A port (red) 2 x USB 3.2 Gen 1 ports 2 x USB 2.0/1.1 ports 1 x HDMI port 1 x DisplayPort 1 x Q-Flash Plus button 1 x RJ-45 port 3 x audio jacks	I/O Con iTE®
		H/W Monitoring Voltage detection	Temperature detection Fan speed detection Water cooling flow rate detection Fan fail warning Fan speed control * Whether the fan speed control function is supported will depend on the fan you install.	BIOS 1 x 2
		Unique Features Support for GIGABYTE Control Center (GCC) * Available applications in GCC may vary by motherboard model. Supported functions of each application may also vary depending on motherboard specifications.	Support for Q-Flash Support for Q-Flash Plus	Bundle Norto Secur
		Operating System Support for Windows 11 64-bit	Support for Windows 10 64-bit	Form F Micro 24.4c